



March 25, 2021

RESIDENT ENGINEER SERVICES FOR BURLINGTON GREENWAY REHABILITATION PHASE 3B SOUTH ~~AND OAKLEDGE FOR ALL~~ ~~UNIVERSAL ACCESS PROJECT~~

Addendum 2

Questions:

1) Please advise whether proposing consultants should include construction oversight services for the playground project, and if so, please advise us on when that project might start and how many weeks of inspection we should include in our cost proposals for the playground.

The playground project is not moving forward yet this season and should not be included in the RE proposal.

2) Is there a separate set of drawings for the Oakledge for All Project, and will your RE be responsible for overseeing that project in addition to Greenway Phase 3b South?

See answer 1 above. The playground project is not moving to construction yet and is no longer part of this RE RFP.

3) Please confirm that consultants should assemble their RE proposals assuming that the entire Greenway reconstruction project will take place in 2021.

The Greenway reconstruction project will be divided and the RE proposals should account for both Sections.

Section 1 of the Greenway reconstruction project for 2021 will consist of the Flynn Avenue intersection/ Oval/ Beach Access and the Gateway at Austin Drive. From approximately STA 121+96.11 to STA. 127+00.00 on the north end (See Sheets 15 +16) and STA 100+15.27 and STA.100+15.27 (See Sheet 12).

Section 2 of the Greenway reconstruction project, which is anticipated to be bid as an ad/alternate at this time, will consist of the remainder of the Greenway: from STA. 110+15.27 to STA. 121+96.11.

1) What is the probable schedule for construction of the project(s)?

The expected start date for the construction project is late-May and needs to be completed by November 2021.

BPRW's estimate of timeframe for the Phase 3b South

Pre-Construction Phase	Construction Phase	Closeout
25 hours	Both Sections: 30 weeks	25 hours

4) How will BPRW handle the approval of Off-Site waste, borrow and staging areas? Will this process be handled by BPRW in-house, or will the VTrans Environmental Unit get involved, as indicated in your RFP?

Task 2: Construction Inspection. Point 3. Reword to:

"Inspect and approve material sources and waste, borrow and staging areas, with due regard to approval/disapproval from the CPM."

6) Will you be issuing one Invitation for Bids to cover both the Greenway Project and the Oakledge for All Playground Project, or will you be procuring two separate construction contracts for the two projects? Depending on the level of construction activity, two separate contracts may necessitate two separate construction inspectors.

The Greenway Project and the Oakledge for All Project will be procured separately. However, we would like to understand how, if needed, how would two REs work together?

7) Your RFP indicates that the Resident Engineer should "coordinate and maintain a schedule with specified milestone dates for the project." Will BPRW be providing the RE with the milestones and their respective dates?

Yes.

8) Why must the CPM review each Daily Work Report before it is distributed? This will delay the distribution of information.

We are flexible and often adjust to particular RE's style.

9) Under Task 2: Construction Inspection, Item #4 asks the RE to geo-locate any and all underground utilities that are encountered during construction and to maintain a set of red-line plans in the BPRW GIS system. Are you looking for digital coordinates for all these utilities? Our experience is that most, if not all, general contractors have GIS technology and use it regularly for layout and construction work. On the other hand, RE consultants typically do not own GIS technology. Would you be amenable to making the contractor(s) responsible for taking GIS "shots" on these utilities? The RE could certainly obtain data from the contractor(s) for plotting those utilities in the as-built drawings.


Yes. We would be amenable to an alternative approach to this as long as the results are the same: geo-location of all underground utilities encountered.

CITY OF BURLINGTON



PROPOSED IMPROVEMENT
BURLINGTON BIKE PATH
REHABILITATION PROJECT
PHASE 3B (SOUTH)

CITY OF BURLINGTON
COUNTY OF CHITTENDEN




FINAL PLANS (90%)
FEBRUARY 2021

PROJECT LOCATION: LOCATED IN THE COUNTY OF CHITTENDEN, CITY OF BURLINGTON, THE PROJECT RUNS FROM AUSTIN DRIVE TO BLANCHARD BEACH.


PROJECT DESCRIPTION: WORK TO BE PERFORMED INCLUDES REMOVAL OF THE EXISTING PATH PAVEMENT; THE WIDENING AND REPAVING OF THE PATH; INSTALLATION OF PAVEMENT MARKINGS, SIGNS, AND CONCRETE SIDEWALK RAMPS; THE RECONFIGURATION OF THE PATH AT THE FLYNN AVENUE INTERSECTION, AND OTHER INCIDENTAL ITEMS.

LENGTH OF PROJECT: SEGMENT 1: 0.51 MILES (2684.73 FEET)
TOTAL: 0.51 MILES (2684.73 FEET)



CONSTRUCTION IS TO BE CARRIED ON IN ACCORDANCE WITH THESE PLANS AND THE VTRANS STANDARD SPECIFICATIONS FOR CONSTRUCTION DATED 2018, INCLUDING ALL SUBSEQUENT REVISIONS AND SUCH REVISED SPECIFICATIONS AND SPECIAL PROVISIONS AS ARE INCORPORATED IN THIS CONTRACT.

SURVEYED BY :		VHB ALDRICH + ELLIOT, PC BUTTON PROFESSIONAL LAND SURVEYORS, PC CROSS CONSULTING ENGINEERS
SURVEYED DATE :		AUGUST 2013, AUG. 2015, SEPTEMBER 2018
DATUM		
VERTICAL		NAVD 88
HORIZONTAL		NAD 83 (07)



PROJECT MANAGER :		EVAN P. DETRICK, P.E.
PROJECT NAME :		BURLINGTON BIKE PATH PHASE 3B
PROJECT NUMBER :		58109.01
SHEET 1 OF 48 SHEETS		

INDEX OF SHEETS

1	TITLE SHEET
2	INDEX OF SHEETS
3	CONVENTIONAL SYMBOLOGY LEGEND
4	PROJECT NOTES
5-6	TYPICAL SECTIONS
7-8	DETAIL SHEETS
9-10	QUANTITY SUMMARY SHEET
11	ALIGNMENT POINTS SHEET
12-16	PLAN AND PROFILE SHEETS
17-19	LANDSCAPE LAYOUT PLAN
20	GRADING PLAN
21-24	LANDSCAPE DETAILS
25-27	PLANTING PLANS
28	PLANTING DETAILS
29	TRAFFIC SIGN SUMMARY SHEET
30	SIGN DETAIL SHEET
31-37	CROSS SECTION SHEETS
38-39	EPSC NARRATIVE
40	EPSC DETAILS
41-45	EPSC PLANS
46-48	TRAFFIC CONTROL PLANS

ADDITIONAL SYMBOLS

EXIST. STREET LIGHT	
EXISTING SURVEY CONTROL POINTS	
PROP. ORNAMENTAL STREET LIGHT	
FIRE CALL BOX	
PROPOSED TREE	
PROPOSED TREE WITH TREE PIT	
PROPOSED SHRUB	
PROPOSED TREE PIT OR TREE LOCATION	
PROPOSED BRICK PAVERS	
EXIST. STORM DRAIN	
EXIST. SEWER	
EXIST. WATER	
EXIST. GAS	
EXIST. UNDERGROUND TELEPHONE	
PROPOSED DRAINAGE CALLOUT	
FIRE HYDRANT	
PROPOSED PULL BOX	
PROPOSED CONDUIT	
PROPOSED CONDUIT AND SLEEVE	
PROPOSED WATER LINE	
PROPOSED SEWER LINE	
PROPOSED ROOF DRAIN	
PROPOSED STORMWATER TREATMENT PLANTER	
PROPOSED BANNER POLE	
BORING LOCATION	
PROPOSED WAYFINDING SIGN	

VAOT STANDARDS

A-78	4-7-2020	SHARED USE PATH TYPICAL
A-79	4-7-2020	RAIL TRAIL TYPICAL
B-5	6-01-1994	SLOPE GRADING, EMBANKMENTS, MUCK
C-3A	4-7-2020	SIDEWALK RAMPS
E-10	4-7-2020	ROLLED EROSION CONTROL PRODUCT, TYPE I
E-15	4-7-2020	SILT FENCE
E-12I	8-8-1995	STANDARD SIGN PLACEMENT - CONVENTIONAL ROAD
E-193	8-18-1995	PAVEMENT MARKING DETAILS
E-195	6-9-2008	SHARED USE PATH PAVEMENT MARKINGS AND SIGN DETAILS
T-1	4-25-2016	TRAFFIC CONTROL GENERAL NOTES
T-2	4-7-2020	TRAFFIC SIGN GENERAL NOTES
T-10	8-6-2012	CONVENTIONAL ROADS CONSTRUCTION APPROACH SIGNING
T-28	8-6-2012	CONSTRUCTION SIGN DETAILS
T-30	8-6-2012	CONSTRUCTION SIGN DETAILS
T-45	1-2-2013	SQUARE TUBE SIGN POST AND ANCHOR



PROJECT NAME:	BURLINGTON BIKE PATH PHASE 3B
PROJECT NUMBER:	58109.01
FILE NAME: 58109ind.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P. DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: B.M.ROBERTS	CHECKED BY: E.P. DETRICK
INDEX OF SHEETS	SHEET 2 OF 48

SYMBOLGY LEGEND NOTE

R. O. W. ABBREVIATIONS (CODES) & SYMBOLS

■	BDNDS	BOUND SET
▣	BDNDS	BOUND TO BE SET
◎	IPNF	IRON PIN FOUND
●	IPNS	IRON PIN TO BE SET
☒	CALC	EXISTING ROW POINT
○	PROW	PROPOSED ROW POINT
[LENGTH]		LENGTH CARRIED ON NEXT SHEET

POINT	CODE	DESCRIPTION
-------	------	-------------

THESE ARE COMMON VAOT SURVEY POINT SYMBOLS FOR EXISTING FEATURES, ALSO USED FOR PROPOSED FEATURES WITH HEAVIER LINEWEIGHT, IN COMBINATION WITH PROPOSED ANNOTATION.

CODE	DESCRIPTION
------	-------------

D	CURVE DEGREE OF (100FT)
R	CURVE RADUIS OF
T	CURVE TANGENT LENGTH
L	CURVE LENGTH OF
E	CURVE EXTERNAL DISTANC

UNDERGROUND UTILITIES

ABOVE GROUND UTILITIES (AERIAL)

PROJECT CONSTRUCTION SYMBOLOGY

— · · — · CZ — · · — · CLEAR ZONE
 _____ PLAN LAYOUT MATCHLINE

	TOP OF CUT SLOPE
	TOE OF FILL SLOPE
	STONE FILL
	BOTTOM OF DITCH
	CULVERT PROPOSED
	STRUCTURE SUBSURFACE
	PROJECT DEMARCATION FENCE
	BARRIER FENCE
	TREE PROTECTION ZONE (TPZ)
	STRIPING LINE REMOVAL
	SHEET PILES

BOUNDARY LINES

PROPERTY LINE (P/L)
 SLOPE RIGHTS
 6F PROPERTY BOUND
 4F PROPERTY BOUND
 HAZARDOUS WASTE



EPSC MEASURES

SEE EPSC DETAIL SHEETS FOR ADDITIONAL SYMBOLOGY

	WETLAND BOUNDARY
	RIPARIAN BUFFER ZONE
	WETLAND BUFFER ZONE
	SOIL TYPE BOUNDARY
	THREATENED & ENDANGERED SPECIES
	HAZARDOUS WASTE AREA
	AGRICULTURAL LAND
	FISH & WILDLIFE HABITAT
	FLOOD PLAIN
	ORDINARY HIGH WATER (OHW)
	STORM WATER
	USDA FOREST SERVICE LANDS
	WILDLIFE HABITAT SUIT/CONN

—— ARCH ——	ARCHEOLOGICAL BOUNDARY
— HISTORIC DIST —	HISTORIC DISTRICT BOUNDARY
—— HISTORIC ——	HISTORIC AREA
(H)	HISTORIC STRUCTURE

EXISTING FEATURES

	RAILROAD TRACKS
	CULVERT (EXISTING)
	STONE WALL
	WALL
	WOOD LINE
	BRUSH LINE
	HEDGE
	BODY OF WATER
	LEDGE EXPOSED

FILE NAME: 58109legend.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P. DETRICK	DRAWN BY: VTRANS
DESIGNED BY: VTRANS	CHECKED BY: E.P. DETRICK
CONVENTIONAL SYMBOLS LEGEND SHEET	SHEET 3 OF 48



PROJECT NOTES

GENERAL

- 1. ALL MATERIALS AND CONSTRUCTION SHALL CONFORM TO THE STATE OF VERMONT AGENCY OF TRANSPORTATION STANDARD SPECIFICATIONS FOR CONSTRUCTION, DATED 2018, AND ITS LATEST REVISIONS.
- 2. PER AMERICANS WITH DISABILITIES ACT ACCESSIBILITY GUIDELINES (ADAAG), PATH CROSS SLOPES SHALL NOT EXCEED 2%.
- 3. ALL SHARED USE PATH LONGITUDINAL RAMPS AT ROADWAY AND DRIVEWAY CROSSINGS SHALL NOT EXCEED 5%.

CONSTRUCTION

- 4. ALL TREE CLEARING AND TREE REMOVAL WITHIN THE SLOPE LIMITS SHOWN ON THE PLANS SHALL BE PAID FOR UNDER ITEM 201.10, "CLEARING AND GRUBBING, INCLUDING INDIVIDUAL TREES AND STUMPS". ADDITIONAL TREE CLEARING AND REMOVAL BEYOND THE SLOPE LIMITS WILL BE PAID UNDER ITEM 201.15, "REMOVING MEDIUM TREES", UNLESS OTHERWISE NOTED IN THESE PLANS.
- 5. ANY EXISTING SIGNS NOT REUSED SHALL REMAIN THE PROPERTY OF THE CITY OF BURLINGTON. THESE SIGNS SHALL BE REMOVED BY THE CONTRACTOR AND STOCKPILED FOR REMOVAL BY THE CITY. STOCKPILE LOCATION TO BE DETERMINED BY THE RESIDENT ENGINEER.
- 6. THE FOLLOWING IS A LIST OF CONTACTS THE CONTRACTOR SHALL NOTIFY AT LEAST SEVEN (7) FULL BUSINESS DAYS PRIOR TO EXCAVATING:

CITY OF BURLINGTON:
CINDI WIGHT, DIRECTOR OF PARKS, RECREATION & WATERFRONT;
(802) 865-7557
JON ADAMS KOLLITZ, BURLINGTON BIKE PATH REHABILITATION PROJECT MANAGER;
(802) 865-7247
CHAPIN SPENCER, DIRECTOR OF PUBLIC WORKS;
(802) 863-9094
CALEB MANNA, ROW AND EXCAVATION INSPECTION, DPW
(802) 865-7562
BURLINGTON ELECTRIC DEPARTMENT:
BRIAN SWEENEY, DISTRIBUTION ENGINEER;
(802) 865-7324

- 7. CONTRACTOR SHALL BE RESPONSIBLE FOR SITE SECURITY AND JOB SAFETY. CONSTRUCTION ACTIVITIES SHALL BE IN ACCORDANCE WITH OSHA STANDARDS, STATE AND LOCAL REQUIREMENTS.
- 8. AREAS OUTSIDE THE LIMITS OF PROPOSED WORK DISTURBED BY THE CONTRACTOR'S OPERATIONS SHALL BE RESTORED BY THE CONTRACTOR TO THEIR ORIGINAL CONDITION AT THE CONTRACTOR'S EXPENSE.
- 9. IN THE EVENT GROSS CONTAMINATED SOIL, GROUNDWATER, AND OTHER MEDIA ARE ENCOUNTERED DURING EXCAVATION AND CONSTRUCTION ACTIVITIES BASED ON VISUAL, OLFACTORY, OR OTHER EVIDENCE, THE CONTRACTOR SHALL STOP WORK IN THE VICINITY OF THE SUSPECT MATERIAL TO AVOID FURTHER SPREADING OF THE MATERIAL, AND SHALL NOTIFY THE RESIDENT ENGINEER IMMEDIATELY SO THAT THE APPROPRIATE TESTING AND SUBSEQUENT ACTION CAN BE TAKEN.
- 10. THERE ARE EXISTING STORM DRAIN LINES LOCATED BENEATH THE PATH. COMPACTION SHALL NOT BE COMPLETED USING VIBRATORY ROLLING METHODS. DAMAGE RESULTING FROM CONTRACTOR CONSTRUCTION LOADS SHALL BE REPAIRED BY THE CONTRACTOR AT NO ADDITIONAL COST TO OWNER.
- 11. CONTRACTOR SHALL CONTROL STORMWATER RUNOFF DURING CONSTRUCTION AS PER THE EPSC NARRATIVE AND DETAILS PROVIDED IN THESE PLANS TO PREVENT ADVERSE IMPACTS TO OFF SITE AREAS, AND SHALL BE RESPONSIBLE TO REPAIR RESULTING DAMAGES, IF ANY, AT NO COST TO OWNER.
- 12. ALL CONTRACTORS WORKING IN DIRECT CONTACT WITH SOILS FOR EXCAVATING, REGRADING, AND OTHER PROJECT TASKS SHALL BE OSHA-HAZWOPER CERTIFIED.
- 13. THE EXISTING WOODEN BIKE PATH SIGNS LOCATED WITHIN THE PROJECT ARE TO BE REMOVED BY THE CONTRACTOR AND STOCKPILED AT THE CITY OF BURLINGTON PARKS, RECREATION & WATERFRONT. PAYMENT WILL NOT BE MADE DIRECTLY, BUT SHALL BE CONSIDERED INCIDENTAL TO ITEM 201.10, "CLEARING AND GRUBBING, INCLUDING INDIVIDUAL TREES AND STUMPS". THE EXISTING ALUMINUM/STEEL SIGNS TO BE REMOVED WILL BE PAID UNDER ITEM 675.50, "REMOVING SIGNS".
- 14. THE CITY RESERVES FIRST RIGHT OF REFUSAL ON ANY ITEMS SALVAGED AS PART OF THE PROJECT.
- 15. ORNAMENTAL BOULDERS ENCOUNTERED ON SITE SHALL NOT BE IMPACTED DURING CONSTRUCTION. DAMAGE TO ORNAMENTAL BOULDERS RESULTING FROM CONSTRUCTION OPERATIONS SHALL BE REPAIRED BY THE CONTRACTOR AT NO ADDITIONAL COST TO OWNER.
- 16. ALL JAPANESE KNOT WEED ENCOUNTERED DURING CONSTRUCTION SHALL BE REMOVED USING A MULTI-PRONGED APPROACH. THE CONTRACTOR SHALL APPLY HERBICIDES SUCH AS ROUNDUP. ADDITIONALLY, THE CONTRACTOR SHALL EXCAVATE OUT THE ROOT SYSTEM AND DIG UP AS MANY RHIZOMES AS POSSIBLE. TO PREVENT SPREADING OF JAPANESE KNOT WEED UPON REMOVAL, THE CONTRACTOR SHALL DISPOSE OF THE SOIL AND PLANT WASTE IN A CONTROLLED MANNER. REMOVAL OF JAPANESE KNOT WEED SHALL BE INCLUDED IN THE PAY ITEM 201.10, "CLEARING AND GRUBBING, INCLUDING INDIVIDUAL TREES AND STUMPS"

- 17. CONTRACTOR SHALL OBTAIN AN EPSC PERMIT THROUGH THE CITY OF BURLINGTON'S WATER RESOURCES DIVISION. TO OBTAIN A PERMIT, THE CONTRACTOR MUST COMPLETE AND SUBMIT THE CITY OF BURLINGTON EPSC PERMIT APPLICATION TO THE WATER RESOURCES DEPARTMENT USING THE CONTACT INFORMATION LISTED BELOW. ADDITIONAL EPSC MEASURES AS REQUIRED BY CITY PERMIT AND/OR THE ENGINEER THAT ARE NOT ITEMS IN THE CONTRACT WILL NOT BE PAID FOR DIRECTLY BUT WILL BE CONSIDERED INCIDENTAL TO THE ALL OTHER CONTRACT ITEMS.

CITY OF BURLINGTON - DEPARTMENT OF WATER RESOURCES:
JAMES SHERRARD, STORMWATER PROGRAM MANAGER;
(802) 863-4501
JSHERRARD@BURLINGTONVT.GOV

- 18. ALL EXCAVATION, PAVING (REMOVAL AND INSTALLATION), AND CONSTRUCTION OPERATIONS TO BE PERFORMED SHALL BE COMPLETED WITH EXTREME CARE TO NOT DAMAGE THE EXISTING TREES AS OUTLINED IN ITEM 900.645, "SPECIAL PROVISION (ROOT PRUNING AND TREE PROTECTION)". THE CONTRACTOR SHALL VISIT THE SITE PRIOR TO BIDDING AND BECOME FAMILIAR WITH EXISTING CLEARANCES TO TREE CANOPIES AND BID THE PROJECT WITH THE UNDERSTANDING THAT ALTERNATIVE EQUIPMENT MAY BE REQUIRED FOR CONSTRUCTION OPERATIONS TO ENSURE NO DAMAGE TO TREES WILL OCCUR. ALL COSTS SHALL BE INCLUDED UNDER APPROPRIATE PAVEMENT, EXCAVATION, AND ROOT PRUNING AND TREE PROTECTION PAY ITEMS FOR PROTECTION OF EXISTING TREES. IF DAMAGE DOES OCCUR TO ANY OF THE EXISTING TREES, ALL COSTS FOR REPLACEMENT TO THE CITY'S SATISFACTION SHALL BE AT THE CONTRACTOR'S EXPENSE.
- 19. ALL RELOCATED BOULDERS ON PROJECT SHALL BE TAKEN FROM OAKLEDGE PARK AND CHOSEN BY THE CITY OF BURLINGTON PARKS, RECREATION & WATERFRONT.

UTILITY


- 20. THE LOCATIONS, SIZES, AND TYPES OF EXISTING UTILITIES ARE SHOWN AS AN APPROXIMATE REPRESENTATION ONLY. THE OWNER OR DESIGN ENGINEER HAVE NOT INDEPENDENTLY VERIFIED THIS INFORMATION AS SHOWN ON THE PLANS. THE UTILITY INFORMATION SHOWN DOES NOT GUARANTEE THE ACTUAL EXISTENCE, SERVICEABILITY, OR OTHER DATA CONCERNING THE UTILITIES, NOR DOES IT GUARANTEE AGAINST THE POSSIBILITY THAT ADDITIONAL UTILITIES MAY BE PRESENT THAT ARE NOT SHOWN ON THE PLANS. PRIOR TO ORDERING MATERIALS AND BEGINNING CONSTRUCTION, THE CONTRACTOR SHALL VERIFY AND DETERMINE THE EXACT LOCATIONS, SIZES, AND ELEVATIONS OF THE POINTS OF CONNECTIONS TO EXISTING UTILITIES AND, SHALL CONFIRM THAT THERE ARE NO INTERFERENCES WITH EXISTING UTILITIES AND THE PROPOSED WORK, INCLUDING WORK WITHIN THE PUBLIC RIGHTS OF WAY.
- 21. IF ANY SURFACE OR SUBSURFACE UTILITIES ARE DAMAGED BY THE CONTRACTOR, THE CONTRACTOR SHALL CONTACT THE UTILITY OWNER AND THE UTILITY SHALL BE RESTORED TO A CONDITION AT LEAST EQUAL TO THAT IN WHICH THEY WERE FOUND IMMEDIATELY. ALL COSTS ASSOCIATED WITH THE RESTORATION OF DAMAGED UTILITIES SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.
- 22. WHERE AN EXISTING UTILITY IS FOUND TO CONFLICT WITH THE PROPOSED WORK, OR EXISTING CONDITIONS DIFFER FROM THOSE SHOWN SUCH THAT THE WORK CANNOT BE COMPLETED AS INTENDED, THE LOCATION, ELEVATION, AND SIZE OF THE UTILITY SHALL BE ACCURATELY DETERMINED AND THE INFORMATION FURNISHED IN WRITING TO THE RESIDENT ENGINEER FOR THE RESOLUTION OF THE CONFLICT.
- 23. THE CONTRACTOR SHALL VERIFY THE LOCATION OF ALL BURIED AND AERIAL UTILITIES AND POLES PRIOR TO STARTING WORK. THE CONTRACTOR SHALL COORDINATE WITH ALL UTILITY OWNERS TO CONFIRM ACTUAL LOCATIONS PRIOR TO CONSTRUCTION.

DIG-SAFE (1-888-344-7233)
- 24. EXISTING RIM ELEVATIONS FOR DRAIN AND SEWER MANHOLES, WATER VALVE COVERS, GAS GATES, ELECTRIC AND TELEPHONE PULL BOXES, AND MANHOLES, AND OTHER SUCH ITEMS WITHIN THE LIMITS OF THE PROPOSED WORK, ARE APPROXIMATE AND SHALL BE SET/RESET AS FOLLOWS:
 - A. PAVEMENTS AND CONCRETE SURFACES: FLUSH
 - B. ALL SURFACES ALONG ACCESSIBLE ROUTES: FLUSH
 - C. LANDSCAPE, TOPSOIL AND SEED, AND OTHER EARTH SURFACE AREAS: ONE INCH ABOVE SURROUNDING AREA AND TAPER EARTH TO THE RIM ELEVATION
- 25. THE USE OF BRICK AND MORTAR TO ADJUST THE ELEVATION OF DRAINAGE OR SANITARY STRUCTURES IS PROHIBITED. ALL ELEVATION ADJUSTMENTS SHALL BE MADE USING EITHER GRADE RINGS OR A SYNTHETIC RISER.
- 26. ALL CONNECTIONS BETWEEN PRECAST DRAINAGE STRUCTURES AND NEW DRAINAGE PIPES SHALL BE A BOOTED CONNECTION.
- 27. CONTRACTOR IS RESPONSIBLE FOR IDENTIFYING AND ADJUSTING ALL CURB STOPS, WATER VALVES, MANHOLES, & DRAINAGE STRUCTURES WITHIN THE PROJECT LIMITS TO THE FINAL GRADE ELEVATION. PAYMENT FOR ADJUSTMENTS SHALL BE PAID FOR UNDER THE APPROPRIATE CONTRACT PAY ITEMS.





PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109notes.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P. DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: B.M.ROBERTS	CHECKED BY: E.P. DETRICK
PROJECT NOTES	SHEET 4 OF 48


MATERIAL TOLERANCES	
MATERIAL ITEM	THICKNESS TOLERANCE
PAVEMENT (FULL DEPTH)	+/- 1/4" (TOTAL THICKNESS)
SUBBASE	1/2"
SAND BORROW	1"



* RESIDENT ENGINEER TO DETERMINE LIMITS OF SIDE PATH
REQUIRED BEFORE MATCHING EXISTING.
** SLOPE TO BE TO BE DETERMINED BY RESIDENT ENGINEER.




* RESIDENT ENGINEER TO DETERMINE LIMITS OF SIDE PATH
REQUIRED BEFORE MATCHING EXISTING.
** SLOPE TO BE TO BE DETERMINED BY RESIDENT ENGINEER.




PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109+typ.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P. DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: B.M.ROBERTS	CHECKED BY: E.P. DETRICK
TYPICAL SECTIONS (2 OF 2)	SHEET 6 OF 48






DETECTABLE WARNING SURFACE
N. T. S.

SECTION A-A
NOT TO SCALE




TYPICAL PATH CENTERLINE PAVEMENT MARKING
N. T. S.



BOULDER RETAINING WALL

N. T. S.
STA. 112+50 - 113+65, LT

NOTE: RETAINING WALL SHALL BE PAID FOR UNDER ITEM 900.670 "SPECIAL PROVISION (BOULDER RETAINING WALL)".



1. SEE VTRANS SPECIFICATION 656.11, TREE PROTECTION, FOR STEPS TO MINIMIZE SOIL AND ROOT DISTURBANCE AND GUIDANCE TO CONSTRUCT PROTECTION MEASURES FOR TREES CLOSE TO CONSTRUCTION AREAS.
2. NO WORK, NOR HEAVY EQUIPMENT STORAGE SHALL BE WITHIN A TREE PROTECTION ZONE.
3. ANY TREE ROOTS ENCOUNTERED WITHIN THE EXCAVATION LIMITS SHALL BE PRUNED AND TREES IDENTIFIED BY THE ENGINEER SHALL BE PROTECTED IN ACCORDANCE WITH, AND PAID FOR UNDER, SPECIAL PROVISION 900.645 (ROOT PRUNING AND TREE PROTECTION).
4. CITY ARBORIST OR BPRW REPRESENTATIVE CAN SPECIFY TREE PROTECTION IN THE DRIPLINE.


TREE PROTECTION
N. T. S.

PROJECT NAME: BURLINGTON BIKE PATH PHASE 3A
PROJECT NUMBER: 58109.00

FILE NAME: 58109det.dgn
PROJECT LEADER: E.P. DETRICK
DESIGNED BY: B.M. ROBERTS
DETAIL SHEET 11 OF 21

PLOT DATE: 2/19/2021
DRAWN BY: C.K. FORD
CHECKED BY: E.P. DETRICK
SHEET 7 OF 48






UNDERDRAIN DETAIL
N. T. S.

NOTE:

PAYMENT FOR GEOTEXTILE FOR UNDERDRAIN TRENCH LINING AND DRAINAGE AGGREGATE IS INCIDENTAL TO ITEM 605.10 "UNDERDRAIN PIPE, 6 INCHES".



STORMWATER DISCONNECTION TREATMENT AREA

N. T. S.

STA. 103+50 - STA. 110+00, RT
STA. 103+50 - STA. 106+00, LT
STA. 108+00 - STA. 110+00, LT
STA. 117+75 - STA. 122+25, RT
STA. 120+00 - STA. 122+50, LT
STA. 125+50 - STA. 127+00, RT

NOTES:

1. WHEN GRADING FOR DISCONNECTION AREAS, THE CONTRACTOR SHALL NOT DISTURB THE GROUND WITHIN 4' OF THE TRUNK BASE FOR ALL TREES WITH A DIAMETER OF 6" OR GREATER AND INTEND TO REMAIN THROUGH CONSTRUCTION.

DISCONNECTION CREDIT REQUIREMENTS

1. THE MAXIMUM CONTRIBUTING FLOW PATH LENGTH ACROSS THE CONTRIBUTING IMPERVIOUS AREA TO A DISCHARGE LOCATION SHALL BE 75 FEET OR LESS.
2. THE AMOUNT OF CONTRIBUTING IMPERVIOUS AREA TO ANY POINT DISCHARGE LOCATION CANNOT EXCEED 1,000 SF.
3. THE LENGTH OF THE "DISCONNECTION" SHALL BE EQUAL TO OR GREATER THAN THE CONTRIBUTING IMPERVIOUS FLOW PATH LENGTH FOR SLOPES 8% OR LESS, AND TWICE THE IMPERVIOUS FLOW PATH LENGTH FOR SLOPES 8% - 15%.
4. RUNOFF CANNOT COME FROM A DESIGNATED HOTSPOT LAND USE.

SOIL DEPTH AND QUALITY STANDARD

THESE REQUIREMENTS APPLY TO ALL DISTURBED AREAS WITHIN THE LIMITS OF THE SITE WHICH ARE NOT COVERED BY AN IMPERVIOUS SURFACE, INCORPORATED INTO A STRUCTURAL STORMWATER TREATMENT PRACTICE, OR ENGINEERED AS STRUCTURAL FILL ONCE DEVELOPMENT IS COMPLETE. FOR THIS PROJECT THESE AREAS INCLUDE THE DISCONNECTION AREAS DISTURBED DURING PATH CONSTRUCTION. A DENSE AND VIGOROUS VEGETATIVE COVER SHALL BE ESTABLISHED OVER TURF AREAS. ANY AREAS NOT DESCRIBED ABOVE WHICH ARE DISTURBED OR COMPACTED DURING CONSTRUCTION SHALL ALSO BE SUBJECT TO THESE REQUIREMENTS.

ALTERNATIVELY, TO LEAVING EXISTING TOPSOIL IN PLACE WITHOUT DISTURBING OR COMPACTING IT, THERE ARE THREE METHODS THAT MAY BE USED TO SATISFY THESE REQUIREMENTS.

1. AMEND EXISTING TOPSOIL IN PLACE
 - A. SCARIFY OR TILL SUBSOILS TO 4 INCHES OF DEPTH OR TO THE DEPTH NEEDED TO ACHIEVE A TOTAL DEPTH OF 8 INCHES OF UNCOMPACTED SOIL AFTER A CALCULATED AMOUNT OF AMENDMENT IS ADDED.
 - B. AMEND THE SOIL TO MEET THE ORGANIC CONTENT REQUIREMENTS. ORGANIC MATERIAL MAY BE PLACED AT A PRE-APPROVED RATE OF 1 INCH WITH AN ORGANIC MATTER CONTENT OF 40-65% AND ROTOTILLED INTO 3 INCHES OF SOIL OR AT A CALCULATED RATE ROTOTILLED INTO A DEPTH OF SOIL NEEDED TO ACHIEVE 4 INCHES OF SETTLED SOIL AT 4% ORGANIC CONTENT.
2. REMOVE AND STOCKPILE EXISTING TOPSOIL DURING GRADING
 - A. TOPSOIL SHOULD BE STOCKPILED ON SITE IN A CONTROLLED AREA AT LEAST 50 FEET FROM SURFACE WATERS, WETLANDS, FLOODPLAINS, OR OTHER CRITICAL RESOURCE AREAS.
 - B. SCARIFY OR TILL SUBGRADE TO A DEPTH OF 4 INCHES. EXCEPT FOR WITHIN THE DRIP LINE OF EXISTING TREES, THE ENTIRE SURFACE SHALL BE DISTURBED BY SCARIFICATION.
 - C. STOCKPILED TOPSOIL SHALL ALSO BE AMENDED, IF NEEDED, TO MEET THE ORGANIC CONTENT REQUIREMENTS IDENTIFIED ABOVE.
 - D. REPLACE STOCKPILED TOPSOIL PRIOR TO PLANTING AND RAKE TO LEVEL, REMOVING ANY SURFACE ROCKS LARGER THAN 2 INCHES IN DIAMETER.
 - E. WATER OR ROLL SOILS IN TURF AREAS TO 85% OF MAXIMUM DRY DENSITY.

3. IMPORT TOPSOIL MIX OF SUFFICIENT ORGANIC CONTENT AND DEPTH
 - A. SCARIFY OR TILL SUBGRADE TO A DEPTH OF 4 INCHES. EXCEPT FOR WITHIN THE DRIP LINE OF EXISTING TREES, THE ENTIRE SURFACE SHALL BE DISTURBED BY SCARIFICATION.
 - B. PLACE 4 INCHES OF IMPORTED TOPSOIL MIX THAT CONTAINS 4% ORGANIC MATTER. SOILS USED IN THE MIX SHALL BE SAND OR SANDY LOAM AS DEFINED BY THE USDA.
 - C. RAKE TO LEVEL, REMOVING ANY SURFACE ROCKS GREATER THAN 2 INCHES IN DIAMETER.
 - D. WATER OR ROLL SOIL IN TURF AREAS TO 85% OF MAXIMUM DRY DENSITY.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR PREPARING AND EXECUTING A PLAN FOR VERIFYING THAT THESE AREAS HAVE MET THIS STANDARD. THIS PLAN SHOULD INCLUDE A MINIMUM OF 9 TEST HOLES PER ACRE OF AREA SUBJECT TO THIS STANDARD. THESE TEST HOLES SHALL BE EXCAVATED TO 8 INCHES USING ONLY A SHOVEL DRIVEN SOLELY BY THE WEIGHT OF THE INSPECTOR AND SHALL BE A MINIMUM OF 50 FEET APART.

PROJECT NAME: BURLINGTON BIKE PATH PHASE 3A	
PROJECT NUMBER: 58109.00	
FILE NAME: 58109det.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: B.M.ROBERTS
DESIGNED BY: B.M.ROBERTS	CHECKED BY: E.P.DETRICK
DETAIL SHEET (2 OF 2)	SHEET 8 OF 48



QUANTITY SHEET 1

SUMMARY OF ESTIMATED QUANTITIES												TOTALS		DESCRIPTIONS				DETAILED SUMMARY OF QUANTITIES			
									FLYNN AVE PAUSE PLACE	BIKE/TRANSP ORTATION PATH	AUSTIN DRIVE GATEWAY	OAKLEDGE PARK PARKING LOT	GRAND TOTAL	FINAL	UNIT	ITEMS	ITEM NUMBER	ROUND	QUANTITIES	UNIT	ITEMS
										1			1		LS	CLEARING AND GRUBBING, INCLUDING INDIVIDUAL TREES AND STUMPS	201.10				
										9			9		EACH	REMOVING MEDIUM TREES	201.15				
								440		1600	50		2090		CY	COMMON EXCAVATION	203.15				
										240			240		CY	EXCAVATION OF SURFACES AND PAVEMENTS	203.28				
										10			10		CY	EARTH BORROW	203.30				
								60		410	15	20	505		CY	SAND BORROW	203.31				
								35		40			75		CY	TRENCH EXCAVATION OF EARTH	204.20				
								40					40		CY	STRUCTURE EXCAVATION	204.25				
								30					30		CY	GRANULAR BACKFILL FOR STRUCTURES	204.30				
										30			30		SY	COARSE-MILLING, BITUMINOUS PAVEMENT	210.10				
								140					140		CY	SUBBASE OF DENSE GRADED CRUSHED STONE (PERMEABLE SUBBASE)	301.35				
								130		1200	25	19	1374		CY	SUBBASE OF DENSE GRADED CRUSHED STONE	301.35				
											5		5		CY	AGGREGATE SURFACE COURSE	401.10				
										15			15		CWT	EMULSIFIED ASPHALT	404.65				
										580			580		TON	MARSHALL BITUMINOUS CONCRETE PAVEMENT	406.25				
								790					790		LB	REINFORCING STEEL, LEVEL I	507.11				
								15					15		CY	CONCRETE, CLASS B	541.25				
										45			45		LF	12" CPEP(SL)	601.2605				
										2			2		EACH	12" CPEPES	601.7005				
										25			25		LF	RE-LAYING PIPE CULVERTS (12" CPEP(SL))	601.99				
								166					166		LF	UNDERDRAIN PIPE, 6 INCHES	605.10				
										180			180		MGAL	DUST CONTROL WITH WATER	609.10				
										220			220		LF	CAST-IN-PLACE CONCRETE CURB, TYPE B	616.28				
								160		140	10	80	390		SY	PORTLAND CEMENT CONCRETE SIDEWALK, 5 INCH	618.10				
										28			28		SF	DETECTABLE WARNING SURFACE	618.30				
										1			1		LS	MOBILIZATION/DEMOBILIZATION	635.11				
										1			1		LS	TRAFFIC CONTROL	641.10				
										700			700		LF	4 INCH YELLOW LINE, WATERBORNE PAINT	646.2111				
										2860			2860		SY	GEOTEXTILE FOR ROADBED SEPARATOR	649.11				
										620			620		LB	SEED	651.15				
										1770			1770		LB	FERTILIZER	651.18				
										8			8		TON	AGRICULTURAL LIMESTONE	651.20				
										1500			1500		CY	TOPSOIL	651.35				
										8			8		TON	HAY MULCH	653.10				
										520			520		SY	ROLLED EROSION CONTROL PRODUCT, TYPE I	653.20				
										50			50		LF	SILT FENCE, TYPE I	653.475				
										1120			1120		LF	SILT FENCE, TYPE II	653.476				
										1330			1330		LF	BARRIER FENCE	653.50				
										3680			3680		LF	PROJECT DEMARCATION FENCE	653.55				
												6	6		EACH	DECIDUOUS TREES	656.30				



QUANTITY SHEET 2

[illegible]

PROJECT NAME:	BURLINGTON BIKE PATH PHASE 3B
PROJECT NUMBER:	58109.01

FILE NAME: 58I09qss.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: C.K.FORD	CHECKED BY: E.P.DETRICK
QUANTITY SUMMARY SHEET (2 OF 2)	SHEET 10 OF 48



SEGMENT 1

POINT	STATION	NORTHING	EASTING
POT	100+15.27	712045.96	1450636.77
POC	127+00.00	714136.37	1451295.94

SEGMENT 1 EXTENDS FROM AUSTIN DRIVE
TO BLANCHARD BEACH.
LENGTH OF SEGMENT 1 = 3659.46 FT

LEGEND

POB POINT OF BEGINNING ALIGNMENT
POE POINT OF END ALIGNMENT

NOTES:

BASLINE STATIONING IS NOT CONTINUOUS.
EQUALITIES HAVE BEEN INCORPORATED INTO THE
BASLINE STATIONING. SEE LAYOUT SHEETS FOR
EQUALITY INFORMATION AND CURVE DATA.

PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B
PROJECT NUMBER: 58109.01

FILE NAME: 58109ali_pt.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: B.M.ROBERTS	CHECKED BY: E.P.DETRICK
ALIGNMENT POINTS SHEET	SHEET II OF 48



CURVE (3)
 DELTA = 35° 51' 00"
 D = 15° 41' 51" (1) D = 1° 08' 45" (2)
 R = 365.00' (1) R = 5000.00' (2)
 T = 146.97' (1) T = 490.38' (2)
 L = 197.18' (1) L = 427.42' (2)
 E = 28.48'

SPECIAL PROVISION
(BURLINGTON GREENWAY SIGN -
IDENTIFICATION SIGN)
STA 100+53, LT

DETECTABLE
WARNING SURFACE
STA 100+17

SEGMENT 1 POB STA 100+00.00

STA 100+21, LT

BEGIN PROJECT
STA. 100+15.27



A stop sign with the letter 'N' above and below it.

— REMOVE OAKLEDGE PARK
SIGN AND RESET AT
STA 100+70, RT

— 11' PAVED PATH WITH
2' AGGREGATE
SHOULDERS ON BOTH
SIDES

REMOVE 3 MAPLE TREES
AND 1 ASH TREE
(INCIDENTAL TO ITEM
201.10)

PROTECT TREES —

REMOVE EXISTING
PAVEMENT. TOPSOIL,
SEED, AND MULCH


CURVE (2)
DELTA = 6°02'37"
D = 28°38'52"
R = 200.00'
T = 10.56'
L = 21.10'
E = 0.28'

REMOVE 1 POTENTIAL
ROOST TREE (PRT)
AND 6 OTHER TREES
(INCIDENTAL TO ITEM
201.10)

End Section 1 -
Austin Drive
Gateway

CURVE (1)
DELTA = 50° 31' 50"
D = 163° 42' 08"
R = 35.00'
T = 16.52'
L = 30.87'
E = 3.70'


SIGNING LEGEND
N = NEW SIGN
R&R = REMOVE AND RESET



THE GRADES SHOWN TO THE NEAREST TENTH ARE THE ORIGINAL
GROUND ELEVATIONS ALONG THE PROPOSED ALIGNMENT.

THE GRADES SHOWN TO THE NEAREST HUNDREDTH ARE THE FINISH GRADES ALONG THE PROPOSED ALIGNMENT.

STATIONING AND ELEVATIONS IN FEET (TYP.)





PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B
PROJECT NUMBER: 58109.01

FILE NAME: 58I09bdr_nul.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: C.K.FORD	CHECKED BY: E.P.DETRICK
PLAN AND PROFILE (SHEET 1 OF 5)	SHEET 12 OF 48








THE GRADES SHOWN TO THE NEAREST TENTH ARE THE ORIGINAL GROUND ELEVATIONS ALONG THE PROPOSED ALIGNMENT.

THE GRADES SHOWN TO THE NEAREST HUNDREDTH ARE THE FINISH GRADES ALONG THE PROPOSED ALIGNMENT.

STATIONING AND ELEVATIONS IN FEET (TYP.)



PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109bdr_nul.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: C.K.FORD	CHECKED BY: E.P.DETRICK
PLAN AND PROFILE (SHEET 4 OF 5)	SHEET 15 OF 48

4 INCH YELLOW LINE, WATERBORNE PAINT
STA 122+50 - 123+07, BL (DASHED)
STA 123+57 - 127+00, BL (DASHED)

UNDERDRAIN PIPE, 6 INCHES
STA 122+75, LT - 123+46, RT
STA 122+97 - 123+68, LT

DETECTABLE WARNING SURFACE
STA 123+25 - 123+41, RT

SPECIAL PROVISION (BURLINGTON GREENWAY
SIGN - IDENTIFICATION SIGN)
STA 122+85, RT
STA 123+81, LT


END PROJECT
STA. 127+00.00

CURVE (13)
DELTA = 21°13'22"
D = 28°38'52"
R = 200.00'
T = 37.47'
L = 74.08'
E = 3.48'

CURVE (12)
DELTA = 22°57'06"
D = 22°55'06"
R = 250.00'
T = 50.75'
L = 100.15'
E = 5.10'

End of Section 1


CURVE (11)
DELTA = 52°23'11"
D = 31°49'52"
R = 180.00'
T = 88.54'
L = 164.58'
E = 20.60'




THE GRADES SHOWN TO THE NEAREST TENTH ARE THE ORIGINAL
GROUND ELEVATIONS ALONG THE PROPOSED ALIGNMENT.

THE GRADES SHOWN TO THE NEAREST HUNDREDTH ARE THE FINISH
GRADES ALONG THE PROPOSED ALIGNMENT.

STATIONING AND ELEVATIONS IN FEET (TYP.)




PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109bdr_nul.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: C.K.FORD	CHECKED BY: E.P.DETRICK
PLAN AND PROFILE (SHEET 5 OF 5)	SHEET 16 OF 48



PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME:	PLOT DATE: 02/18/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: M.K.WILLARD
DESIGNED BY: M.K.WILLARD	CHECKED BY: E.P.DETRICK
LANDSCAPE LAYOUT PLAN	SHEET 17 OF 48






PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B
PROJECT NUMBER: 58109.01

FILE NAME:
PROJECT LEADER: E.P.DETRICK
DESIGNED BY: M.K.WILLARD
LANDSCAPE LAYOUT PLAN

PLOT DATE: 02/18/2021
DRAWN BY: M.K.WILLARD
CHECKED BY: E.P.DETRICK
SHEET 18 OF 48






PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B
PROJECT NUMBER: 58109.01

FILE NAME:
PROJECT LEADER: E.P.DETRICK
DESIGNED BY: M.K.WILLARD
LANDSCAPE LAYOUT PLAN

PLOT DATE: 02/18/2021
DRAWN BY: M.K.WILLARD
CHECKED BY: E.P.DETRICK
SHEET 19 OF 48





PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B
PROJECT NUMBER: 58109.01


FILE NAME:
PROJECT LEADER: E.P.DETRICK
DESIGNED BY: M.K.WILLARD
GRADING PLAN

PLOT DATE: 02/18/2021
DRAWN BY: M.K.WILLARD
CHECKED BY: E.P.DETRICK
SHEET 20 OF 48



NOTES:

1. CONTRACTOR SHALL INSTALL A PAVER EDGE RESTRAINT WHEN PAVERS ARE NEXT TO SOFTSCAPE AREAS (PLANTING BEDS, LAWN, ETC.)




C SPECIAL PROVISION (PERMEABLE PAVERS)

SCALE 1" = 1'-0"

NOTES:

1. CONSTRUCT SUBBASE BASED ON "PATH TYPICAL SECTION", REFER TO TYPICAL SECTIONS




B CONCRETE SIDEWALK

SCALE 1" = 1'-0"

NOTES:

1. CONSTRUCT SUBBASE BASED ON "PATH TYPICAL SECTION", REFER TO TYPICAL SECTIONS




A SPECIAL PROVISION (PORTLAND CEMENT CONCRETE SIDEWALK, EXPOSED AGGREGATE SURFACE)

SCALE 1" = 1'-0"

NOTES:

1. REFER TO LAYOUT PLANS FOR LOCATION AND DIMENSIONS OF LANDING.
2. DOWEL EACH LANDING TO THE NEIGHBORING STAIR FOUNDATION OR CONCRETE WALK, REFER TO ISOLATION JOINT DETAIL.




D CONCRETE LANDING

SCALE 1" = 1'-0"


E



PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME:	PLOT DATE: 02/18/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: M.K.WILLARD
DESIGNED BY: M.K.WILLARD	CHECKED BY: E.P.DETRICK
LANDSCAPE DETAILS	SHEET 21 OF 48




B 14" CONCRETE TREAD W / 6" RISER
SCALE 1" = 1'-0"



A HANDRAIL POST ANCHOR
SCALE 3" = 1'-0"

- NOTES:
1. CONTRACTOR SHALL VERIFY NUMBER OF TREADS AND RISERS ON THE LAYOUT AND GRADING PLANS.
 2. CONTRACTOR SHALL PROVIDE SHOP DRAWINGS FOR HANDRAILS FOR REVIEW AND APPROVAL.
 3. ALL REINFORCING IN THE STAIRS, AND STAIR FOUNDATIONS SHALL MEET THE REQUIREMENTS OF SECTION 507 FOR LEVEL I REINFORCING, AND SHALL BE UNCOATED. PAYMENT FOR REINFORCING WILL BE MADE UNDER ITEM 507.11, "REINFORCING STEEL, LEVEL I".
 4. ALL CONCRETE IN THE STAIRS, AND STAIR FOUNDATIONS SHALL MEET THE REQUIREMENTS OF SECTION 541 FOR CLASS B CONCRETE. PAYMENT FOR CONCRETE WILL BE MADE UNDER ITEM 541.25, "CONCRETE, CLASS B".
 5. CLEAR COVER SHALL BE 3" UNLESS OTHERWISE NOTED.
 6. MATERIAL MEETING THE REQUIREMENTS OF SUBSECTION 704.02, WITH GRADATION FOR 3/4" STONE, MAY BE SUBSTITUTED FOR GRANULAR BACKFILL FOR STRUCTURES AND WILL BE PAID FOR UNDER ITEM 204.30, "GRANULAR BACKFILL FOR STRUCTURES".




C SECTION: CONCRETE STEPS AND RAMPS
SCALE: 1/2" = 1'-0"

PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B
PROJECT NUMBER: 58109.01


FILE NAME:
PROJECT LEADER: E.P.DETRICK
DESIGNED BY: M.K.WILLARD
LANDSCAPE DETAILS

PLOT DATE: 02/18/2021
DRAWN BY: M.K.WILLARD
CHECKED BY: E.P.DETRICK
SHEET 22 OF 48








NOTES:
1. COLOR TO BE BLACK POWDER COAT.
2. LOCATIONS TO BE VERIFIED BY LANDSCAPE ARCHITECT PRIOR TO INSTALLATION.
3. INSTALL PER MANUFACTURER'S RECOMMENDATIONS.



NOTES:
1. COLOR TO BE BLACK POWDER COAT.
2. LOCATION TO BE VERIFIED BY LANDSCAPE ARCHITECT PRIOR TO INSTALLATION.
3. REFER TO SPECIFICATIONS.




B BIKE RACK

SCALE 1" = 1'

A BIKE TUNING STATION

SCALE 1" = 1'

NOTES:
1. BOULDERS WILL BE SELECTED BY LANDSCAPE ARCHITECT OR BPRW.
2. BOULDERS VARY IN SIZE.
3. LANDSCAPE ARCHITECT TO ASSIST CONTRACTOR IN FIELD SETTING ALL BOULDERS. FINAL PLACEMENT TO BE APPROVED BY LANDSCAPE ARCHITECT OR BPRW.




C SPECIAL PROVISION (LANDSCAPE BOULDER)

SCALE 1/2" = 1'-0"


PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME:	PLOT DATE: 02/18/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: M.K.WILLARD
DESIGNED BY: M.K.WILLARD	CHECKED BY: E.P.DETRICK
LANDSCAPE DETAILS	SHEET 23 OF 48






NOTES:
1. asdfasdfsdf

A OVAL LAYOUT - AUSTIN DRIVE
SCALE 1/4" = 1'-0"



B OVAL LAYOUT - OAKLEDGE
SCALE 1/4" = 1'-0"



NOTES:
1.) ALL STL. MEMBERS COATED W/ ZINC RICH EPOXY THEN FINISHED W/ POLYESTER POWDER COATING.
2.) 1/2" X 3 3/4" EXPANSION ANCHOR BOLTS PROVIDED
3.) BENCH IS SHIPPED UNASSEMBLED.

LENGTH OPTIONS:
☐ 6" BENCH
☐ 8" BENCH

DuMor, inc. P.O. Box 142 Mifflintown, PA 17059-0142	SCALE : NONE	TITLE : BENCH		
	DATE DRAWN : 3/22/04	REV.	DRAWING NUMBER	SHEET
	DRAWN BY : AH	G	93 SERIES	1 OF 2
	DATE REV. : 5/7/08			
	REV. BY : AH			


C BENCH
NTS

NOTES:
1. BENCH LENGTH TO BE 6 FEET
2. COLOR TO BE BLACK POWDER COAT
3. REFER TO LANDSCAPE PLANS FOR LOCATION
4. INSTALL BENCH PER MANUFACTURER'S RECOMMENDATIONS.

NOTES:
1. THE BPRW LOGO IS TO BE SAND BLASTED INTO THE EXPOSED AGGREGATE CONCRETE. CONTRACTOR SHALL PROVIDE SANDED BLASTED EXAMPLES FOR REVIEW AND APPROVAL.
2. DESIGN TEAM WILL PROVIDE AN ELECTRONIC LAYOUT OF THE BPRW LOGO TO ASSIST IN DEVELOPING A TEMPLATE FOR THE LOGO OUTLINE.
3. INFILL THE SAND BLASTED LOGO WITH BLACK MONUMENT PAINT. CONTRACTOR SHALL PROVIDE SUBMITTAL FOR REVIEW AND APPROVAL.



PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME:	PLOT DATE: 02/18/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: M.K.WILLARD
DESIGNED BY: M.K.WILLARD	CHECKED BY: E.P.DETRICK
LANDSCAPE DETAILS	SHEET 24 OF 48




PLANT SCHEDULE

SHRUBS	QTY	BOTANICAL NAME	COMMON NAME	SIZE
CA2	28	Cornus stolonifera 'Arctic Fire'	Arctic Fire Dogwood	18" - 24" SPD
PN2	8	Physocarpus opulifolius	Ninebark	18" - 24" SPD
GRASSES	QTY	BOTANICAL NAME	COMMON NAME	SIZE
CA	41	Calamagrostis x acutiflora 'Karl Foerster'	Karl Foerster Feather Reed Grass	2 GAL.
PVS	30	Panicum virgatum 'Shenandoah'	Shenandoah Switch Grass	2 GAL.
SH	64	Sporobolus heterolepis	Prairie Dropseed	2 GAL.

Notes:
Refer to planting details, notes and specifications for plant material installation requirements.

PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME:	PLOT DATE: 02/18/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: M.K.WILLARD
DESIGNED BY: M.K.WILLARD	CHECKED BY: E.P.DETRICK
PLANTING PLAN	SHEET 25 OF 48





PLANT SCHEDULE

DECIDUOUS TREES	QTY	BOTANICAL NAME	COMMON NAME	SIZE
	6	Acer x freemanii 'Sienna'	Sienna Glen Maple	2 1/2 - 3" CAL.
GRASSES	QTY	BOTANICAL NAME	COMMON NAME	SIZE
	8	Calamagrostis x acutiflora 'Karl Foerster'	Karl Foerster Feather Reed Grass	2 GAL.
	13	Panicum virgatum 'Shenandoah'	Shenendoah Switch Grass	2 GAL.
PVS	12	Sporobolus heterolepis	Prairie Dropseed	2 GAL.

Notes:
Refer to planting details, notes and specifications for plant material installation requirements.

PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME:	PLOT DATE: 02/18/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: M.K.WILLARD
DESIGNED BY: M.K.WILLARD	CHECKED BY: E.P.DETRICK
LANDSCAPE PLAN	SHEET 26 OF 48





PLANT SCHEDULE


SHRUBS	QTY	BOTANICAL NAME	COMMON NAME	SIZE
CA2	9	Cornus stolonifera 'Arctic Fire'	Arctic Fire Dogwood	18" - 24" SPD
GRASSES	QTY	BOTANICAL NAME	COMMON NAME	SIZE
CA	15	Calamagrostis x acutiflora 'Karl Foerster'	Karl Foerster Feather Reed Grass	2 GAL.
DS	15	Deschampsia cespitosa 'Schottland'	Schottland Hair Grass	2 GAL.
PVS	6	Panicum virgatum 'Shenandoah'	Shenandoah Switch Grass	2 GAL.
SH	18	Sporobolus heterolepis	Prairie Dropseed	2 GAL.

Notes:
Refer to planting details, notes and specifications for plant material installation requirements.

PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME:	PLOT DATE: 02/18/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: M.K.WILLARD
DESIGNED BY: M.K.WILLARD	CHECKED BY: E.P.DETRICK
PLANTING PLAN	SHEET 27 OF 48




NOTES:
1. QUANTITY OF SHRUBS AND SPACING
AS NOTED IN PLANTING SCHEDULE.
2. ALL PLANTING BEDS ARE TO BE CONTINUOUS, COMPLETELY
DUG OUT AND BACKFILLED WITH THE PROPER LANDSCAPE BACKFILL



C SHRUB PLANTING

SCALE: 1/2" = 1'-0"



D PERENNIAL PLANTING

N.T.S.

- NOTES:
1. REFER TO PLANTING PLAN FOR SPACING AND QUANTITIES.
 2. ALL PLANTING BEDS ARE TO BE CONTINUOUS, COMPLETELY DUG OUT AND BACKFILLED WITH THE PROPER PLANTING BED BACKFILL MATERIAL, REFER TO SOIL PREPARATION SPECIFICATION.

SURROUNDING SOIL SHOULD NOT EXCEED 80% COMPACTION, DRAINAGE WILL BE REQUIRED IF COMPACTED SOILS ARE PRESENT

NYLON STRAP WITH 3/4" GROMMETS, REFER TO SPECIFICATIONS INCIDENTAL TO DECIDUOUS TREES, ITEM 656.30

FASTEN WIRE BELOW POINT OF MAJOR BRANCHING OR TO MAJOR OUTSIDE TRUNK.


2 1/2" HARDWOOD STAKES. ALIGN STAKES PARALLEL W/ ROAD/ WALKS OR PARALLEL W/ DIRECTION OF PREVAILING WIND, REFER TO TREE STAKING DETAIL INCIDENTAL TO DECIDUOUS TREES, ITEM 656.30

TEMPORARY WATERING BASIN MADE FROM SOIL

BREAK APART EDGE OF EXCAVATION W/ SHOVEL AND BLEND PLANT MIX W/ EXISTING SOIL TO PROVIDE TRANSITION TO UNDISTURBED GRADE

UNDISTURBED GRADE


EXCAVATE ONLY TO SPECIFIED PLANTING DEPTH TO ENSURE STABLE BASE



- NOTES:
1. EXAMINE ENTIRE TREE AND REMOVE ALL NURSERY TAGS, ROPE, STRING, OR SURVEYORS TAPE TO PREVENT FUTURE GIRDLING.
 2. ALL TREE PLANTING BEDS ARE TO BE CONTINUOUS, COMPLETELY DUG OUT AND BACKFILLED WITH THE PROPER PLANTING BED BACKFILL MATERIAL, REFER TO SOIL PREPARATION SPECIFICATION.
 3. WIDTH OF TREE PIT SHALL BE 3 TIMES THE DIAMETER OF THE ROOT BALL, UNLESS TREE IS BEING PLANTED IN CONTINUOUS LANDSCAPE BEDS / PITS.

A TREE PLANTING

SCALE 1/4" = 1'-0"



B TREE STAKING LAYOUT

NO SCALE

PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B

PROJECT NUMBER: 58109.01

FILE NAME:

PROJECT LEADER: E.P.DETRICK

DESIGNED BY: M.K.WILLARD

PLANTING DETAILS

PLOT DATE: 02/18/2021



DRAWN BY: M.K.WILLARD

CHECKED BY: E.P.DETRICK


SHEET 28 OF 48







TRAFFIC SIGN SUMMARY SHEET


MILE MARKER, STATION, OR SIGN NUMBER	SIGN LEGEND	SIGN DIMENSIONS			NEW & SALVAGED SIGNS				EXIST POST RE TAIN S AL V A G E	NO. OF P O S T S	FLANGED CHANNEL			SQUARE STEEL (IN)			TUBULAR ALUMINUM Ø (IN)			WOOD POST (LF)		W-SHAPE STEEL				RE FR A M E S I G N E D	REMARKS	SIGN DETAIL			
																												EA	WIDTH (IN)	HEIGHT (IN)	"A"
		OPTION ITEMS																													
100+21, LT		I	18	18	2.25					I				X			X												R1-1 MOUNTED ON NEW POST		SHSM
AUSTIN DRIVE		I	30	14	2.92					I				X+			X												MOUNTED ON NEW POST WOG	THIS SHEET	
FINAL POST LENGTHS ARE TO BE DETERMINED IN THE FIELD. POST SIZES ARE COMPUTED BASED ON INFORMATION FURNISHED ON THE STANDARD SHEETS AND THE ROADWAY, TRAFFIC & SAFETY DIVISION'S "SIGN POST DESIGN GUIDELINE."											FT	FT	FT	FT	FT	FT		EA	LB	LB	LB		TYPE 1	TYPE 2					BOY = BLACK LEGEND ON YELLOW BACKGROUND - PLAQUE BOW = BLACK LEGEND ON WHITE BACKGROUND - PLAQUE GOW = GREEN LEGEND ON WHITE BACKGROUND - PLAQUE ROW = RED LEGEND ON WHITE BACKGROUND - PLAQUE WOB = WHITE LEGEND ON BLUE BACKGROUND - PLAQUE WOG = WHITE LEGEND ON GREEN BACKGROUND FYG = BLACK LEGEND ON FLUORESCENT YELLOW-GREEN BACKGROUND SHSM = FHWA STANDARD HIGHWAY SIGNS AND MARKINGS BOOK (WITH 2012 SUPPLEMENT)		
TOTALS					SF	SF	EA.	SF			FT	FT			25			LB	EA.	WOOD POSTS (FT)		EA.	EA.	LB							

POST LENGTH AVERAGES 10 FEET
POST LENGTH WITH '+ ' AVERAGES 15 FEET







4 Section
Scale: 3" = 1' - 0"



5 Graphic Detail
Scale: 3" = 1' - 0"




1A Side A
Scale: 3/4" = 1' - 0"



1B Side A
Scale: 3/4" = 1' - 0"



2 Side B
Scale: 3/4" = 1' - 0"



3 Top (Cap Removed)
Scale: 3/4" = 1' - 0"

BIKE PATH IDENTIFICATION SIGN DETAILS


NOT TO SCALE

NOTES:


- BIKE PATH IDENTIFICATION SIGNS MUST COMPLY WITH WAYFINDING GUIDELINES
FOUND AT:
<https://enjoyburlington.com/resources/brand-wayfinding-guidelines/>
- TEXT STYLE TO BE TITLE CASE WITH FONT "IDEAL SANS MEDIUM".




PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109sign_det.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P. DETRICK	DRAWN BY: C.K. FORD
DESIGNED BY: C.K. FORD	CHECKED BY: E.P. DETRICK
SIGN DETAIL SHEET	SHEET 30 OF 48




101+00




100+50




100+00




102+50




102+00




101+50



104+00




103+50




103+00




PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109xs.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: B.M.ROBERTS
DESIGNED BY: B.M.ROBERTS	CHECKED BY: E.P.DETRICK
SECTION 1CROSS SECTIONS (1 OF 7)	SHEET 31 OF 48




105+50




107+00




108+50




105+00




106+50




108+00



104+50




106+00




107+50

PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109xs.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: B.M.ROBERTS
DESIGNED BY: B.M.ROBERTS	CHECKED BY: E.P.DETRICK
SECTION 1CROSS SECTIONS (2 OF 7)	SHEET 32 OF 48







110+00




109+50




109+00




111+50




111+00




110+50



113+00




112+50




112+00




PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109xs.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: B.M.ROBERTS
DESIGNED BY: B.M.ROBERTS	CHECKED BY: E.P.DETRICK
SECTION 1CROSS SECTIONS (3 OF 7)	SHEET 33 OF 48




114+00




115+50




117+00




113+75




115+00




116+50



113+50




114+50




116+00

PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109xs.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: B.M.ROBERTS
DESIGNED BY: B.M.ROBERTS	CHECKED BY: E.P.DETRICK
SECTION 1 CROSS SECTIONS (4 OF 7)	SHEET 34 OF 48







118+50




120+00




121+50




118+00




119+50




121+00



117+50




119+00




120+50




PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109xs.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: B.M.ROBERTS
DESIGNED BY: B.M.ROBERTS	CHECKED BY: E.P.DETRICK
SECTION 1CROSS SECTIONS (5 OF 7)	SHEET 35 OF 48




123+00




124+50




126+00




122+50




124+00




125+50



122+00




123+50




125+00




PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109xs.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: B.M.ROBERTS
DESIGNED BY: B.M.ROBERTS	CHECKED BY: E.P.DETRICK
SECTION 1CROSS SECTIONS (6 OF 7)	SHEET 36 OF 48




127+50




127+00




126+50




128+50




128+00



130+00



129+50



129+00



PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109xs.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: B.M.ROBERTS
DESIGNED BY: B.M.ROBERTS	CHECKED BY: E.P.DETRICK
SECTION 1 CROSS SECTIONS (7 OF 7)	SHEET 37 OF 48

EROSION CONTROL NARRATIVE

1. PROJECT DESCRIPTION

THIS PROJECT INVOLVES THE REMOVAL OF EXISTING PAVEMENT ON THE BURLINGTON BIKE PATH BETWEEN AUSTIN DRIVE AND BLANCHARD BEACH; THE WIDENING AND REPAVING OF THE PATH; INSTALLATION OF PAVEMENT MARKINGS, SIGNS, AND CONCRETE SIDEWALK RAMPS; THE RECONFIGURATION OF THE FLYNN AVENUE INTERSECTION; AND THE CONSTRUCTION OF STORMWATER DISCONNECTION TREATMENT AREAS.

2. AREA OF TOTAL DISTURBANCE

AS SHOWN ON THE ATTACHED EPSC PLAN THE TOTAL PROJECT AREA OF DISTURBANCE IS APPROXIMATELY **2.98 ACRES**.

AREA OF DISTURBANCE INCLUDES LIMITS OF EARTH DISTURBANCE WITHIN THE PROJECT AREA. A SPECIFIC STAGING AREA IS NOT ANTICIPATED FOR THIS PROJECT. STAGING IS ANTICIPATED TO OCCUR WITHIN PERMITTED PROJECT LIMITS BASED ON THE CURRENT PHASE OF CONSTRUCTION. THE PROJECT LIMITS ARE SHOWN ON THE ATTACHED EPSC PLAN.

SUPPORT ACTIVITIES OUTSIDE THE APPROVED PROJECT BOUNDARIES (I.E., WASTE OR BORROW AREAS, STAGING AREAS) ARE NOT INCLUDED IN THE TOTAL ABOVE AND, IF REQUIRED, SHALL OBTAIN COVERAGE BY AMENDING THE PERMIT OR BY OBTAINING COVERAGE UNDER A DIFFERENT PERMIT.

3. SEQUENCE OF MAJOR PROJECT COMPONENTS

THE CONTRACTOR SHALL SEQUENCE CONSTRUCTION ACTIVITIES TO MINIMIZE, TO THE GREATEST EXTENT POSSIBLE, DISTURBED SOIL LEFT OPEN TO EROSION AT ANY GIVEN TIME. TOTAL EARTH DISTURBANCE AT ANY ONE TIME THROUGHOUT THE SITE SHALL BE LIMITED TO **2 ACRES** OR LESS. ALL EARTH DISTURBANCE SHALL BE TEMPORARILY STABILIZED WITHIN **7 CALENDAR DAYS**. IT IS ANTICIPATED THAT THIS PROJECT WILL LAST ONE CONSTRUCTION SEASON.

4. STABILIZATION OF EXPOSED SOILS

THE MAXIMUM AREA OF CONCURRENT EARTH DISTURBANCE IS **2 ACRES**, WHILE IMPLEMENTING THE PERMITTED EPSC PLAN TO MINIMIZE POTENTIAL FOR EROSION AND SEDIMENT TRANSPORT ASSOCIATED WITH OPEN AREAS. THE TOTAL DURATION OF EXPOSED SOIL WILL BE **7 DAYS** FROM INITIAL DISTURBANCE, WHILE IMPLEMENTING THE PERMITTED EPSC PLAN TO TEMPORARILY OR PERMANENTLY STABILIZE AREAS AS SOON AS PRACTICABLE.

- SEED AND MULCH WILL BE USED FOR BOTH PERMANENT AND TEMPORARY STABILIZATION MEASURES. ROLLED EROSION CONTROL PRODUCT (RECP) WILL BE USED IN PLACE OF MULCH FOR SLOPES GREATER THAN 1V:3H. MULCH IS TO BE APPLIED AT A MINIMUM APPLICATION RATE SHOWN IN TURF ESTABLISHMENT DETAIL, UNLESS DIRECTED OTHERWISE BY THE ENGINEER.
- DISTURBED AREAS AND SOIL STOCKPILES THAT WILL NOT BE WORKED FOR MORE THAN 7 DAYS SHALL BE TEMPORARILY STABILIZED WITH SEED AND MULCH/RECP WITHIN 48 HOURS.
- EXPOSED AREAS THAT HAVE ACHIEVED FINAL GRADE SHALL BE PERMANENTLY STABILIZED WITHIN 48 HOURS.
- IN AREAS WHERE VEGETATIVE COVER WILL PROVIDE PERMANENT STABILIZATION, SEEDING TO BE COMPLETED BETWEEN APRIL 15 AND SEPTEMBER 15.
- SLOPES GREATER THAN 2H:1V SHALL BE TREATED WITH STONE FILL, TYPE I.

5. VEGETATED BUFFERS

THE VEGETATION IN THE PROJECT AREA CONSISTS OF GRASSED SLOPES WITH MINIMAL TREE COVERAGE. THE IMPACT TO VEGETATION WILL BE LIMITED TO THAT WHICH IS DIRECTLY AFFECTED BY THE RECONSTRUCTION AND WIDENING OF THE PATH AND EXTENDING SLOPES AS REQUIRED. DISTURBED VEGETATION WILL BE REESTABLISHED WITH STANDARD SEED AND MULCH PRACTICES. STRAW MULCH SHALL BE USED IN WETLAND, WETLAND BUFFER AREAS AND GRAVEL WETLANDS.

6. DRAINAGE AREAS AND RECEIVING WATERS

THE PROJECT SITE IS LOCATED IN THE UPPER LAKE CHAMPLAIN WATERSHED. THE PROJECT DRAINS VIA DIRECT CONVEYANCE TO LAKE CHAMPLAIN.

THE PROJECT AREA HAS BEEN DIVIDED INTO 1 DRAINAGE AREA. DISTURBANCE AND SOIL TYPE PER DRAINAGE AREA IS SUMMARIZED BELOW.

DRAINAGE AREA	SOIL TYPE	NRCS ERODIBILITY (K-VALUE)	AREA OF DISTURBANCE (ACRES)
1	FARMINGTON EXTREMELY ROCKY LOAM, 5-20% SLOPES	0.28	1.661
	COVINGTON SILTY CLAY	0.49	0.112
	VERGENNES CLAY, 2-6% SLOPES	0.49	0.890
	ALLUVIAL LAND	0.10	0.311
	WATER	-	0.003

7. WASTE, BORROW, AND STAGING AREAS

- A SPECIFIC STAGING AREA IS NOT ANTICIPATED FOR THIS PROJECT. STAGING IS ANTICIPATED TO OCCUR WITHIN PERMITTED PROJECT LIMITS BASED ON THE CURRENT PHASE OF CONSTRUCTION.
- WASTE MATERIAL AND EXCESS SOIL NOT ABLE TO BE USED ON-SITE SHALL BE DISPOSED OF AT AN OFF-SITE LOCATION IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS, ORDINANCES AND STATUES. ALL EROSION PREVENTION AND SEDIMENT CONTROL MEASURES NECESSARY FOR WASTE, BORROW, AND STAGING AREAS OUTSIDE THE PROJECT LIMITS SHALL BE PAID FOR PER 105.29 OF THE STANDARD SPECIFICATIONS FOR CONSTRUCTION.
- LOCATE ADDITIONAL AREAS FOR DISPOSAL OF STUMPS, EXCESS SOILS AND COLLECTED SEDIMENT, IF NECESSARY. DISPOSE OF THESE MATERIALS IN A MANNER THAT WILL NOT RESULT IN SEDIMENTS ENTERING WATERS OF THE STATE.
- DISPOSAL SITES REQUIRE RELATIVELY LEVEL TERRAIN WITH AN ISOLATION DISTANCE OF AT LEAST 100 FEET FROM ANY SURFACE WATERS, INCLUDING WETLANDS.
- VEHICLE AND EQUIPMENT STORAGE AREAS OR AREAS ADJACENT TO CONSTRUCTION TRAILERS OR OTHER HIGH TRAFFIC AREAS SHALL BE COVERED WITH GEOTEXTILE FABRIC AND 1 FT OF GRAVEL. FOLLOWING COMPLETION OF CONSTRUCTION, ALL NON-NATIVE MATERIALS SHALL BE REMOVED FROM THE STAGING AREA. COMPACTED, RUTTED, OR OTHERWISE DISTURBED SOILS SHALL BE TILLED, RAKED, SEEDED AND MULCHED.
- ERODIBLE MATERIALS STOCKPILED WITHIN THE MATERIAL STORAGE AREAS SHALL BE ISOLATED WITH SILT FENCE OR OTHER ACCEPTABLE SEDIMENT BARRIER. SOIL STOCKPILED ON THE SITE SHALL BE SEEDED AND MULCHED.

8. WINTER CONSTRUCTION REQUIREMENTS

IN THE EVENT THAT CONSTRUCTION ACTIVITIES CONTINUE INTO THE WINTER CONSTRUCTION SEASON (OCTOBER 15 - APRIL 15), DEPENDING ON ACTUAL FIELD AND WEATHER CONDITIONS THE CONTRACTOR SHALL FOLLOW REQUIREMENTS FOR WINTER CONSTRUCTION, AS DEFINED IN SPECIFIC PERMIT CONDITIONS AND AS FOLLOWS:

- ENLARGED ACCESS POINTS, STABILIZED TO PROVIDE FOR SNOW STOCKPILING.
- LIMITS OF DISTURBANCE MOVED OR REPLACED TO REFLECT BOUNDARY OF WINTER WORK.
- DEVELOPMENT OF A SNOW MANAGEMENT PLAN THAT INCLUDES:
 - ADEQUATE STORAGE AND CONTROL OF MELT-WATER
 - STORAGE OF CLEARED SNOW TO BE PLACED DOWN SLOPE OF DISTURBED AREAS AND OUT OF STORMWATER TREATMENT STRUCTURES
- A MINIMUM 25-FOOT BUFFER SHALL BE MAINTAINED FROM PERIMETER CONTROLS.
- IN AREAS OF DISTURBANCE WITHIN 100 FEET OF A RECEIVING WATER, SILT FENCE SHALL BE REINFORCED OR ELSE REPLACED WITH PERIMETER DIKES, SWALES, OR OTHER PRACTICES RESISTANT TO THE FORCES OF SNOW LOADS.
- DRAINAGE STRUCTURES MUST BE KEPT OPEN AND FREE OF SNOW AND ICE DAMS.
- SILT FENCE AND OTHER PRACTICES REQUIRING EARTH DISTURBANCE MUST BE INSTALLED AHEAD OF FROZEN GROUND.
- MULCH TO BE APPLIED AT TWICE THE REGULAR RATE OR MINIMUM 3-INCH COVER, UNLESS DIRECTED OTHERWISE BY THE ENGINEER.
- AREAS OF DISTURBED SOILS MUST BE STABILIZED AT THE END OF EACH WORK DAY, WITH THE FOLLOWING EXCEPTIONS:
 - IF NO PRECIPITATION WITHIN 24 HOURS IS FORECAST AND WORK WILL RESUME IN THE SAME AREA WITHIN 24 HOURS.
 - DISTURBED AREAS THAT COLLECT AND RETAIN RUNOFF, SUCH AS OPEN UTILITY TRENCHES, MUST BE STABILIZED AT THE END OF EACH WORK WEEK.
- PRIOR TO STABILIZATION, SNOW OR ICE MUST BE REMOVED TO LESS THAN 25MM (1-INCH) THICKNESS.
- STONE STABILIZATION, 10 - 20 FEET WIDE IN AREAS WHERE CONSTRUCTION VEHICLE TRAFFIC IS ANTICIPATED

CONTRACTOR RESPONSIBILITIES, LIMITATIONS & PROHIBITIONS

1. GENERAL NOTES

- IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO AMEND/UPDATE ALL PLANS AND EXISTING PERMITS WHEN ADDING DETAILED CONSTRUCTION PHASING OR ANYTHING ELSE THAT MAY DEVIATE FROM THE APPROVED PLANS AS DIRECTED BY THE RESIDENT ENGINEER.
- OTHER THAN THOSE SHOWN ON THE PLANS ALL LAND DISTURBANCES WITHIN 50 FEET OF ALL WATER BODIES, MEASURED FROM THE TOP OF BANK, AND WETLANDS, ARE PROHIBITED WITHOUT FURTHER REGULATORY REVIEW.
- CONTRACTOR TO MAINTAIN ALL EXISTING STREAMS AND RIPARIAN BUFFER ZONES IN THEIR NATURAL CONDITION.
- OFF-SITE DISCHARGES OF ANY MATERIAL OTHER THAN STORMWATER, SUCH AS VEHICLE AND EQUIPMENT MAINTENANCE SPILLS, FUELS, WASH WATER, CONSTRUCTION DEBRIS, OIL, WET CONCRETE (INCLUDING WASHOUT WATER FROM CONCRETE BATCH TRUCKS OR EQUIPMENT USED TO MIX CONCRETE), AND OTHER SUBSTANCES, ARE PROHIBITED.

- THE FAILURE TO PROMPTLY ABATE THE DISCHARGE OF SEDIMENT OR ANY OTHER WASTE WHICH CAUSES A VISIBLE DISCOLORATION OF SURFACE WATERS (INCLUDING WETLANDS), OR IS FOUND TO BE VIOLATING WATER QUALITY STANDARDS BASED ON MONITORING, IS PROHIBITED. ANY CORRECTIVE ACTION UNDERTAKEN TO REMOVE SEDIMENT FROM A WETLAND IS ALSO PROHIBITED.
- WEATHER CONDITIONS WILL BE MONITORED DURING THE CONSTRUCTION SEASON. IF AN EXTENDED RAIN PERIOD OR HEAVY RAIN IS PREDICTED, EXPOSED SOIL AREAS WILL BE MULCHED PRIOR TO AND DAILY DURING THE RAIN EVENT. IF DETERMINED NECESSARY BY THE RESIDENT ENGINEER, WORK MAY BE SUSPENDED OR LIMITED DURING THE STORM.

2. EPSC PLAN

THE EPSC PLAN HAS BEEN PREPARED USING GENERAL PERMIT 3-9020, PART 4.1(C) AND APPENDIX B OF THE GENERAL PERMIT 3-9020 AS GUIDANCE IN PREPARING THE PLAN. THE FOLLOWING SECTIONS ADDRESS REQUIRED EPSC PLAN NARRATIVE ELEMENTS IN THE ORDER THAT THEY ARE PRESENTED IN APPENDIX B OF GENERAL PERMIT 3-9020.

- THE NAME AND DAYTIME PHONE NUMBER OF THE OSPC SHALL BE PROVIDED IN WRITING TO VT DEC PRIOR TO THE START OF CONSTRUCTION.
- THE NOTICE OF AUTHORIZATION (NOA) ISSUED BY VT DEC SHALL BE POSTED IN A LOCATION THAT IS VISIBLE TO THE PUBLIC (E.G., NEAR THE CONSTRUCTION ENTRANCE).
- A COPY OF THE EPSC PLAN SHALL BE MAINTAINED ON-SITE DURING NORMAL WORKING HOURS FROM THE DATE OF COMMENCEMENT OF CONSTRUCTION ACTIVITIES TO THE DATE OF FINAL STABILIZATION. THE EPSC PLAN SHALL BE MADE AVAILABLE TO VT DEC UPON REQUEST
- EXISTING VEGETATION SHALL BE PROTECTED AND MAINTAINED TO THE EXTENT PRACTICABLE.
- A VEGETATED BUFFER SHALL BE MAINTAINED FOR WATER RESOURCES (E.G., WETLANDS AND STREAMS) TO THE EXTENT PRACTICABLE.
- TO THE EXTENT PRACTICABLE, SURFACE FLOW SHALL BE DIVERTED AWAY FROM EXPOSED SOILS AND WATER RESOURCES.
- RESOURCE AREAS (E.G. STREAMS) WITHIN THE PROJECT AREA SHALL BE FLAGGED PRIOR TO ANY CONSTRUCTION RELATED ACTIVITIES OCCURRING WITHIN CLOSE PROXIMITY TO THOSE AREAS.
- EFFLUENT FROM DEWATERING OPERATIONS SHALL BE FILTERED OR PASSED THROUGH A SEDIMENT TRAPPING DEVICE AND DISCHARGED IN A MANNER THAT DOES NOT RESULT IN IMPACTS TO WATER QUALITY OR CONTRIBUTE TO EROSION. SEE DETAILS FOR MORE INFORMATION.
- SEDIMENT REMOVED FROM SEDIMENT CONTROL PRACTICES SHALL BE DISPOSED OF IN AN UPLAND AREA WITH STABILIZATION FOLLOWING DISPOSAL OF MATERIAL.
- IN ADVANCE OF FORECASTED RAINFALL OR SNOWMELT, EPSC MEASURES THAT ARE LOCATED IN AREAS OF ACTIVE EARTH DISTURBANCE SHALL BE INSPECTED AND REPAIRED, AS NEEDED.
- DUST CONTROL SHALL BE HANDLED VIA WATER OR CALCIUM CHLORIDE APPLICATION TO ROADWAYS AND OTHER AREAS WHERE DUST MAY BE GENERATED.
- STABILIZED CONSTRUCTION ENTRANCES SHALL BE LOCATED AT ALL VEHICLE ACCESS POINTS TO PUBLIC ROADWAYS AND ARE TO BE REGULARLY MAINTAINED TO CONTROL EQUIPMENT AND VEHICLES FROM TRACKING MATERIAL OFF SITE.
- PERIMETER CONTROLS (E.G. SILT FENCE) SHALL BE INSTALLED ON THE DOWNSLOPE SIDE OF AREAS WHERE THERE IS POTENTIAL FOR SILT EROSION AND/OR SEDIMENT RUNOFF. IN SOME AREAS WHERE THE GROUND SURFACE IS LEVEL AND THERE ARE NO PATHWAYS (E.G. DITCHES OR RUTS) THAT COULD TRANSPORT RUNOFF FROM THE PROJECT AREA, INSTALLATION OF PERIMETER CONTROLS MAY NOT BE NECESSARY PER APPROVAL BY THE ON-SITE PLAN COORDINATOR (OSPC)
- CONSTRUCTION DEMARCATION SHALL COMPLY WITH THE FOLLOWING:
 - CONSTRUCTION DEMARCATION TO BE INSTALLED ALONG PERIMETER OF LIMITS OF DISTURBANCE PER THE EPSC PLANS
 - WITHIN 100 FEET OF RESOURCE AREA DEMARCATION MUST INCLUDE:
 - 2 TO 3 ROWS OF STAKED (OR STAPLED) 3-INCH (MIN.) ORANGE BARRIER MESH TAPE,
 - ORANGE CONSTRUCTION FENCE, OR
 - ORANGE SNOW FENCE
 - WHEN GREATER THAN 100 FEET FROM A RESOURCE AREA DEMARCATION MAY INCLUDE:
 - ONE ROW OF STAKED (OR STAPLED) 3-INCH (MIN.) ORANGE BARRIER MESH TAPE,
 - ORANGE CONSTRUCTION FENCE, OR
 - ORANGE SNOW FENCE

PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109epsc_nar.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: C.K.FORD	CHECKED BY: E.P.DETRICK
EPSC NARRATIVE (SHEET 1 OF 2)	SHEET 38 OF 48



- PERIMETER CONTROLS SHALL COMPLY WITH THE FOLLOWING:
 - PERIMETER CONTROLS ARE TO BE INSTALLED ON THE DOWNSLOPE SIDE OF AREAS OF DISTURBANCE WHERE THERE IS POTENTIAL FOR SEDIMENT RUNOFF AND/OR SOIL EROSION.
 - PERIMETER CONTROLS ARE NOT TO CROSS ACTIVE ACCESS ROUTES OR PERENNIAL FLOW PATHS (E.G. A STREAM).
 - PARTICULAR CARE IS TO BE TAKEN WHEN INSTALLING PERIMETER CONTROLS IN A WETLAND.
 - WITHIN 100 FEET OF A WATER RESOURCE AREA, PERIMETER CONTROLS MUST INCLUDE:
 - REINFORCED SILT FENCE - TO BE REINFORCED WITH WIRE MESH, STAKED HAY BALES, OR STAKED FIBER ROLLS.
 - WHEN GREATER THAN 100 FEET FROM A WATER RESOURCE AREA, PERIMETER CONTROLS MAY INCLUDE:
 - SILT FENCE (NON-REINFORCED), OR
 - STAKED FIBER ROLLS
- PROJECT DEMARCATION OF AN AREA SHALL BE INSTALLED PRIOR TO EARTH DISTURBING ACTIVITIES WITHIN THAT AREA. AN EXCEPTION IS LAND DISTURBANCE THAT MAY BE NEEDED TO ACCESS THE AREA WITH EQUIPMENT IN OR TO INSTALL THE EPSC MEASURES.

1. INSPECTION & MONITORING NOTES

OSPC INSPECTION REQUIREMENTS:

- EPSC INSPECTION, MONITORING, AND REPORTING ARE REQUIRED PER THE GENERAL PERMIT 3-9020. THE CONTRACTOR IS RESPONSIBLE FOR INSPECTING AND MAINTAINING EROSION PREVENTION AND SEDIMENT CONTROLS THAT MINIMIZE OR ELIMINATE POLLUTANTS IN STORMWATER DISCHARGE.
- INSPECTIONS BY THE ON-SITE PLAN COORDINATOR (OSPC) SHALL BE CONDUCTED AT LEAST ONCE EVERY SEVEN (7) CALENDAR DAYS, WITH ADDITIONAL INSPECTION FREQUENCY REQUIRED FOR RAIN EVENTS, WINTER CONSTRUCTION, AND VISIBLE DISCHARGES PER THE CONDITIONS OF GENERAL PERMIT 3-9020. A WRITTEN REPORT SHALL BE COMPLETED FOR EACH INSPECTION AND SIGNED BY THE OSPC. ALL REPORTS ARE TO BE MAINTAINED ON SITE AND MADE AVAILABLE TO STATE DEC REPRESENTATIVES UPON REQUEST.
- IF VISIBLY DISCOLORED STORMWATER RUNS OFF THE CONSTRUCTION SITE OR RUNS OFF THE CONSTRUCTION SITE AND DISCHARGES TO RECEIVING WATERS, THE CONTRACTOR SHALL TAKE IMMEDIATE CORRECTIVE ACTION TO CORRECT THE DISCHARGES, INCLUDING MAINTAINING EXISTING EPSC MEASURES, AND INSTALLING SUPPLEMENTAL EPSC MEASURES.
- THE OSPC IS RESPONSIBLE FOR MONITORING, INSPECTING, AND SAMPLING DISCHARGES FROM THE SITE TO MAINTAIN COMPLIANCE WITH GENERAL PERMIT 3-9020. THIS INCLUDES VISUAL MONITORING OF EPSC MEASURES AND DISCHARGES, DISCHARGE SAMPLING, TURBIDITY MONITORING, AND REPORTING. THE MAXIMUM TURBIDITY PERMISSIBLE FOR CONSTRUCTION SITE DISCHARGE IS 25 NTU.
- THE CONTRACTOR SHALL KEEP ONE (1) TURBIDITY MONITOR ONSITE AND HAVE PERSONNEL ON HAND THAT ARE TRAINED IN ITS OPERATION.

ON-SITE PLAN COORDINATOR (OSPC) NOTES:

- THE OSPC DESIGNATED TO THE PROJECT (AND HIS/HER DESIGNEE) SHALL:
 - REVIEW VT DEC’S “ON-SITE PLAN COORDINATOR MANUAL”,
 - BE ON-SITE ON A DAILY BASIS (OR HAVE A DESIGNEE THAT IS ON SITE WHEN HE/SHE CANNOT BE),
 - BE DIRECTLY RESPONSIBLE FOR ON-SITE IMPLEMENTATION OF THE EPSC PLAN,
 - BE KNOWLEDGEABLE IN THE PRINCIPLES AND PRACTICES OF EPSC,
 - POSSESS THE SKILLS TO ASSESS CONDITIONS AT THE CONSTRUCTION SITE THAT COULD IMPACT STORMWATER QUALITY,
 - POSSESS THE SKILLS TO ASSESS THE EFFECTIVENESS OF EPSC MEASURES SELECTED TO CONTROL THE QUALITY OF STORMWATER DISCHARGES FROM CONSTRUCTION ACTIVITY,
 - POSSESSES THE SKILLS AND EQUIPMENT TO CONDUCT TURBIDITY MONITORING PURSUANT TO THE CONSTRUCTION STORMWATER DISCHARGE PERMIT, AND
 - HAVE THE AUTHORITY TO STOP AND/OR MODIFY CONSTRUCTION ACTIVITIES AS NECESSARY TO COMPLY WITH THE EPSC PLAN AND THE CONSTRUCTION STORMWATER DISCHARGE PERMIT.
- ALL PROPOSED CHANGES TO THE EPSC PLAN MUST BE APPROVED BY THE OSPC OR HIS/HER DESIGNEE, THE PLAN DESIGNER OR CERTIFIED PROFESSIONAL IN EROSION AND SEDIMENT CONTROL (CPESC) PRIOR TO IMPLEMENTATION, AND BE CONSIDERED MINOR AMENDMENTS AS DEFINED IN THE OSPC HANDBOOK. ALL MINOR AMENDMENTS ARE TO BE RECORDED USING THE MINOR AMENDMENT RECORD FORM AND MARKED ON THE MASTER OSPC PLAN SET. ALL MODIFICATIONS THAT FALL OUTSIDE OF THE MINOR AMENDMENT DEFINITION MUST BE APPROVED BY VT-DEC.
- DURING THE REGULAR CONSTRUCTION SEASON (APRIL 15 TO OCT 15), THE OSPC OR HIS/HER DESIGNEE SHALL CONDUCT INSPECTIONS AT LEAST ONCE EVERY SEVEN (7) CALENDAR DAYS AND WITHIN 24 HRS FOLLOWING A STORM EVENT RESULTING IN DISCHARGE OF STORMWATER FROM THE CONSTRUCTION SITE.
- THE OSPC AND HIS/HER DESIGNEE(S) SHALL FOLLOW TURBIDITY MONITORING PROTOCOLS OUTLINED IN VT DEC’S “MONITORING OF TURBIDITY IN STORMWATER RUNOFF FROM CONSTRUCTION ACTIVITIES” MANUAL.

- INSPECTIONS CONDUCTED BY THE OSPC OR HIS/HER DESIGNEE SHALL COVER ALL AREAS OF SITE THAT ARE BEING ACTIVELY DISTURBED BY CONSTRUCTION OR CONSTRUCTION -RELATED ACTIVITIES, INCLUDING AREAS THAT HAVE BEEN TEMPORARILY STABILIZED.
- OSPC INSPECTIONS SHALL BE DOCUMENTED USING THE VT DEC INSPECTION REPORT FORM OR A VT DEC-ACCEPTED INSPECTION REPORT FORM.
- OSPC INSPECTION REPORTS SHALL BE MAINTAINED ON-SITE FOR THE DURATION OF THE PROJECT AND MADE AVAILABLE TO VT DEC UPON REQUEST.



PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109epsc_nar.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: C.K.FORD	CHECKED BY: E.P.DETRICK
EPSC NARRATIVE (SHEET 2 OF 2)	SHEET 39 OF 48

CITY OF BURLINGTON RURAL SEED MIX		
	LBS/AC	
% WEIGHT	HYDROSEED	NAME
5%	196.0	MIRCOCOLVER
5%	196.0	BIRDS FOOT TREFOIL
65%	196.0	FINE FESCUE *
20%	196.0	PERENNIAL RYE GRASS
5%	196.0	COLONIAL BENTGRASS

CITY OF BURLINGTON URBAN AREA MIX					
	LBS/AC				
% WEIGHT	BROADCAST	HYDROSEED	NAME	GERM %	PURITY %
40.0%	70	140	CREeping RED FESCUE	85%	98%
30.0%	52.3	104.6	PERENNIAL RYE GRASS	90%	95%
30.0%	52.3	104.6	KENTUCKY BLUE GRASS	85%	85%
0.0%	0	0	ANNUAL RYE GRASS	85%	95%
100%	174.6	349.2			


SOIL AMENDMENT GUIDANCE					
FERTILIZER			LIME		
BROADCAST	HYDROSEED		BROADCAST	HYDROSEED	
10-20-10	FOLLOW		PELLETIZED	FOLLOW	
1000 5 LBS/AC	MANUFACTURER	4	5 TONS/AC	MANUFACTURER	

CONSTRUCTION GUIDANCE

- 1.CITY OF BURLINGTON RURAL SEED MIX: TO BE PAID FOR UNDER ITEM NO. 651.15. USE AS INDICATED IN THE PLANS AND/OR FOR ALL ESTABLISHED UPLAND (NON WETLAND) AREAS DISTURBED BY THE CONTRACTOR.
- 2.URBAN SEED MIX: USE AS INDICATED IN THE PLANS AND/OR FOR ALL ESTABLISHED LAWN AREAS DISTURBED BY THE CONTRACTOR.
- 3.ALL SEED MIXTURES: SHALL NOT HAVE A WEED CONTENT EXCEEDING 0.40% BY WEIGHT AND SHALL BE FREE OF ALL NOXIOUS SEED.
- 4.FERTILIZER AND LIMESTONE: SHALL FOLLOW RATES SHOWN ON PLAN OR AS DIRECTED BY THE ENGINEER
- 5.HAY MULCH: TO BE PLACED ON EARTH SLOPES AT THE RATE OF 4 TONS/ACRE, ACHIEVE 90% GROUND COVER OR AS DIRECTED BY THE ENGINEER.
- 6.TOPSOIL: TO BE USED WITH SEED AS INDICATED ON THE PLANS, OR AS DIRECTED BY THE ENGINEER.
- 7.HYDROSEEDING: ALTHOUGH GUIDANCE IS GIVEN ABOVE THE SITE CONDITIONS AND THE TYPE OF HYDROSEED WILL ULTIMATELY DICTATE THE AMOUNTS AND TYPES OF SOIL AMENDMENTS TO BE APPLIED
- 8.TURF ESTABLISHMENT: PLACING SEED, FERTILIZER, LIME AND MULCH PRIOR TO SEPTEMBER 15 AND AFTER APRIL 15 CAN BETTER ENSURE A VIGOROUS GROWTH OF GRASS.

TURF ESTABLISHMENT

* FINE FESCUE SHALL BE COMPRISED OF THE FOLLOWING SEED BY % WEIGHT:
20% CHEWINGS FESCUE
25% STRONG FESCUE
10% SLENDER FESCUE
10% HARD FESCUR



CONSTRUCTION SPECIFICATIONS

- 1.EROSION MATTING, CHECK SLOTS, SHALL BE SPACED IN DITCH CHANNEL SO THAT ONE OCCURS WITHIN EACH 50' ON SLOPES OF MORE THAN 4% AND LESS THAN 6%. ON SLOPES OF 6% OR MORE, THEY SHALL BE SPACED SO THAT ONE OCCURS WITHIN EACH 25'.
- 2.APPLY FERTILIZER, LIME SEED PRIOR TO PLACING MATTING.
- 3.STAPLES ARE TO BE PLACED ALTERNATELY, IN COLUMNS APPROXIMATELY 2' APART AND IN ROWS APPROXIMATELY 3' APART. APPROXIMATELY 175 STAPLES ARE REQUIRED PER 4'X225' ROLL OF MATERIAL AND 125 STAPLES ARE REQUIRED PER 4'X150' ROLL OF MATERIAL.
- 4.DISTURBED AREAS SHALL BE SMOOTHLY GRADED. EROSION CONTROL MATERIAL SHALL BE PLACED LOOSELY OVER GROUND SURFACE. DO NOT STRETCH.
- 5.ALL TERMINAL ENDS AND TRANSVERSE LAPS SHALL BE STAPLED AT APPROXIMATELY 12" INTERVALS.

ADAPTED FROM DETAILS PROVIDED BY: NEW YORK STATE DEC
ORIGINALLY DEVELOPED BY USDA-NRCS
VERMONT DEPARTMENT OF ENVIRONMENTAL CONSERVATION

ROLLED EROSION
CONTROL PRODUCT
(RECP) DITCH


NOTES:

REFER TO "THE VERMONT STANDARDS & SPECIFICATIONS FOR EROSION PREVENTION & SEDIMENT CONTROL -2006- "FROM THE VT AGENCY OF NATURAL RESOURCES FOR ADDITIONAL GUIDANCE.

THIS WORK SHALL BE PERFORMED IN ACCORDANCE WITH SECTION 653 AND AS SHOWN IN THE PLANS FOR ROLLED EROSION CONTROL PRODUCT, TYPE I(PAY ITEM 653.20) OR ROLLED EROSION CONTROL PRODUCT, TYPE II(PAY ITEM 653.21).

REVISIONS

MARCH 8, 2007	JMF
APRIL 16, 2007	WHF
JANUARY 13, 2009	WHF



CONSTRUCTION SPECIFICATIONS

- 1.APPLY TO SLOPES GREATER THAN 3H: 1V OR WHERE NECESSARY TO AID IN ESTABLISHING VEGETATION.
- 2.APPLY FERTILIZER, LIME SEED PRIOR TO PLACING MATTING.
- 3.STAPLES ARE TO BE PLACED ALTERNATELY, IN COLUMNS APPROXIMATELY 2' APART AND IN ROWS APPROXIMATELY 3' APART. APPROXIMATELY 175 STAPLES ARE REQUIRED PER 4'X225' ROLL OF MATERIAL AND 125 STAPLES ARE REQUIRED PER 4'X150' ROLL OF MATERIAL.
- 4.DISTURBED AREAS SHALL BE SMOOTHLY GRADED. EROSION CONTROL MATERIAL SHALL BE PLACED LOOSELY OVER GROUND SURFACE. DO NOT STRETCH.
- 5.ALL TERMINAL ENDS AND TRANSVERSE LAPS SHALL BE STAPLED AT APPROXIMATELY 12" INTERVALS.

ADAPTED FROM DETAILS PROVIDED BY: NEW YORK STATE DEC
ORIGINALLY DEVELOPED BY USDA-NRCS
VERMONT DEPARTMENT OF ENVIRONMENTAL CONSERVATION

ROLLED EROSION
CONTROL PRODUCT
(RECP) SIDE SLOPE

NOTES:

REFER TO "THE VERMONT STANDARDS & SPECIFICATIONS FOR EROSION PREVENTION & SEDIMENT CONTROL -2006- "FROM THE VT AGENCY OF NATURAL RESOURCES FOR ADDITIONAL GUIDANCE.

THIS WORK SHALL BE PERFORMED IN ACCORDANCE WITH SECTION 653 AND AS SHOWN IN THE PLANS FOR ROLLED EROSION CONTROL PRODUCT, TYPE I(PAY ITEM 653.20) OR ROLLED EROSION CONTROL PRODUCT, TYPE II(PAY ITEM 653.21).

REVISIONS

APRIL 16, 2007	JMF
JANUARY 13, 2009	WHF




PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B

PROJECT NUMBER: 58109.01

FILE NAME: 58109epsc_det.dgn
PROJECT LEADER: E.P. DETRICK
DESIGNED BY: B.O. CRONIN
EPSC DETAILS


PLOT DATE: 2/19/2021
DRAWN BY: B. O. CRONIN
CHECKED BY: E.P. DETRICK
SHEET 40 OF 48





BEGIN PROJECT
STA. 100+15.27

REMOVE EXISTING
PAVEMENT. TOPSOIL,
SEED, AND MULCH



COVINGTON SILTY CLAY
K = 0.49




FILE NAME: 58I09bdr_epsc.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: C.K.FORD	CHECKED BY: E.P.DETRICK
EPSC PLANS (SHEET 10F 5)	SHEET 41 OF 48




PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109bdr_epsc.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: C.K.FORD	CHECKED BY: E.P.DETRICK
EPSC PLANS (SHEET 2 OF 5)	SHEET 42 OF 48



PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109bdr_epsc.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: C.K.FORD	CHECKED BY: E.P.DETRICK
EPSC PLANS (SHEET 3 OF 5)	SHEET 43 OF 48



PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109bdr_epsc.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: C.K.FORD	CHECKED BY: E.P.DETRICK
EPSC PLANS (SHEET 4 OF 5)	SHEET 44 OF 48



PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B	
PROJECT NUMBER: 58109.01	
FILE NAME: 58109bdr_epsc.dgn	PLOT DATE: 2/19/2021
PROJECT LEADER: E.P.DETRICK	DRAWN BY: C.K.FORD
DESIGNED BY: C.K.FORD	CHECKED BY: E.P.DETRICK
EPSC PLANS (SHEET 5 OF 5)	SHEET 45 OF 48

GENERAL

1. THE FOLLOWING TRAFFIC CONTROL INFORMATION IS INTENDED TO BE A CONCEPTUAL NARRATIVE FOR HOW THE WORK MAY PROCEED. THE CONTRACTOR SHALL SUBMIT A DETAILED TRAFFIC CONTROL PLAN TO THE RESIDENT ENGINEER FOR APPROVAL. THE CONTRACTOR SHALL ALLOW AT LEAST TWO (2) WEEKS FOR REVIEW AND APPROVAL. MODIFICATIONS TO THE APPROVED TRAFFIC CONTROL PLAN SHALL BE SUBMITTED TO THE RESIDENT ENGINEER AT LEAST ONE WEEK PRIOR TO THE IMPLEMENTATION OF THE CHANGE.

2. THE CONTRACTOR'S TRAFFIC CONTROL PLAN SHALL BE DEVELOPED IN ACCORDANCE WITH THE 2018 EDITION OF VTRANS STANDARD SPECIFICATIONS SECTION 641 - TRAFFIC CONTROL AND IN SUBSTANTIAL CONFORMANCE WITH THE 2009 EDITION OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) WITH LATEST INTERIMS. THE TRAFFIC CONTROL PLAN SHALL INCLUDE ALL TEMPORARY SIGNS, PAVEMENT MARKINGS, BARRICADES, AND OTHER DEVICES REQUIRED TO PROVIDE COMPLETE MANAGEMENT OF TRAFFIC. ANY SIGNS NOT INCLUDED IN THE FHWA STANDARD HIGHWAY SIGNS BOOK SHALL INCLUDE SIGN FACE DIMENSIONS AND LAYOUT.

3. TRAFFIC CONTROL PLANS SHALL BE ESTABLISHED TO MAINTAIN THE CONTINUITY OF TRAFFIC THROUGH THE CORRIDOR. TRAFFIC CONTROL SIGNS SHALL BE ADJUSTED AT THE COMPLETION OF EACH CONSTRUCTION PHASE AS DIRECTED BY THE RESIDENT ENGINEER. SIGNING, AND OTHER SUPPORTING TRAFFIC CONTROLS DEVICES SHALL BE MAINTAINED THROUGHOUT CONSTRUCTION. INSTALLING, MAINTAINING, ADJUSTING, MODIFYING, AND REMOVING THE TRAFFIC CONTROL DEVICES SHALL BE INCLUDED IN THE UNIT PRICE BID FOR CONTRACT ITEM 641.10 TRAFFIC CONTROL.

4. TRAFFIC SHALL NOT BE CHANGED FROM ONE PHASE TO THE NEXT UNTIL ALL TEMPORARY SIGNING WORK REQUIRED FOR THE SUBSEQUENT PHASE IS COMPLETED. ANY CONFLICTING PAVEMENT MARKINGS SHALL BE MASKED WITH PAVEMENT MARKING MASK OR REMOVED BY GRINDING. EXISTING PAVEMENT MARKINGS THAT ARE TO REMAIN FOR LATER USE SHALL BE MASKED WITH PAVEMENT MARKING MASK.

5. EXISTING SIGNS SHALL REMAIN UNTIL THEY ARE NO LONGER REQUIRED. EXISTING SIGNS WHICH CONFLICT WITH TEMPORARY TRAFFIC CONTROLS SHALL BE COMPLETELY COVERED WITH SOLID COVERS PAINTED BLACK OR REMOVED/RELOCATED AS NEEDED. TEMPORARY SIGNS SHALL BE INSTALLED AS SHOWN IN THE CONTRACTOR'S APPROVED TRAFFIC CONTROL PLANS. NEW SIGNING SHALL BE INSTALLED AS IT BECOMES APPLICABLE. ALL PROPOSED SIGNING SHALL BE INSTALLED AND ALL SIGNS TO BE REMOVED SHALL BE REMOVED PRIOR TO THE APPLICATION OF THE FINAL PAVEMENT MARKINGS.


6. ALL SIGNS SHALL BE LOCATED SO THEY ARE VISIBLE AND ABLE TO BE READ BY THE TRAVELING PUBLIC. SIGNS SHALL BE INSTALLED SO AS NOT TO OBSTRUCT EXISTING SIGNS.

7. ALL SIGNS AND BARRICADES SHALL BE INSPECTED AND REPAIRED DAILY. ALL SIGNS SHALL BE CLEANED OF DUST AND DEBRIS WEEKLY.

8. THE CONTRACTOR SHALL BE RESPONSIBLE FOR INSTALLING AND MAINTAINING ALL SIGNAGE.

9. THE CONTRACTOR SHALL PROVIDE AN 8-FOOT HIGH TEMPORARY CHAIN LINK FENCE BEHIND THE TYPE III BARRICADES TO COMPLETELY BLOCK OFF PUBLIC ACCESS AT EACH END OF THE WORK AREAS INCLUDING ALL SIDE ROAD INTERSECTIONS. THE COST OF THE TEMPORARY CHAIN LINK FENCE IS INCIDENTAL TO ITEM 641.10 "TRAFFIC CONTROL".

10. THE CONTRACTOR SHALL COORDINATE EXACT LOCATIONS AND TYPES OF SIGNS POSTS WITH DANIEL HILL OF DPW TRAFFIC DIVISION; (802)863-9094.



MOUNT ON TYPE III BARRICADE

* LOCATION TO BE DETERMINED BY THE RESIDENT ENGINEER

TRAFFIC CONTROL PLAN
FOR SIDE PATHS
N. T. S.

PROJECT NAME: BURLINGTON BIKE PATH PHASE 3B
PROJECT NUMBER: 58109.01

FILE NAME: 58109+tcp.dgn
PROJECT LEADER: E.P. DETRICK
DESIGNED BY: C.K.FORD
TRAFFIC CONTROL PLAN (1 OF 3)

PLOT DATE: 2/19/2021
DRAWN BY: C.K.FORD
CHECKED BY: E.P. DETRICK
SHEET 46 OF 48



